



## V7 UPS 600VA Desktop UPS

### UPS1P600E

SKU: CA08356

The 600VA Desktop UPS by V7 protects your electronic equipment from damage due to power outages, surges and spikes while providing short term battery power during an outage. Featuring Automatic Voltage Regulation (AVR), which instantly adjusts high and low voltages to safe levels for your electronics, so you can work indefinitely through sustained fluctuations. Specifically designed to protect your equipment and network connection in harsh power environments, the 600VA Deskop UPS ensures maximum productivity and work efficiency.

- LCD Indicator and Audible Status Alarms
- Automatic Voltage Regulation (AVR) instantly corrects voltage fluctuations
- 4 battery backup and surge protected IEC C13 outlets
- Includes: UK and EU Power Cords and two IEC320 C14 (M) to C13 Cables

#### General

Sku: CA08356  
 Model: UPS1P600E  
 EAN: 0662919109337  
 Warranty: 3 Year (1 Year Battery)  
 Compliance: CE, REACH, RoHS  
 Country Of Origin: China  
 Package Type: 4 Color Box  
 SAP: 4938673  
 Package Includes: 2 IEC-IEC cables & (EU/UK) power cables, USB Cable, user's manual, warranty and compliance docs

#### Color

Color: Black

#### Design

UPS Style: Desktop

#### Other

Assurance: up to 75.000 € connected equipment assurance  
 Software: ViewPower for viewing, controlling, and monitoring your UPS systems and automatic computer shutdown. Shutdown Wizard for standalone software allowing automatic computer shutdown

#### Package Dimensions

Package Dimensions (L/W/H): 344 x 140 x 220 mm  
 Shipping Weight: 4.8kg

#### Product Dimensions

Product Dim (L/W/H): 300 x 101 x 142 mm  
 Product Weight: 4.2kg

#### Technical

Voltage: 220/230/240 VAC  
 Battery Type: Sealed Lead Acid  
 Outlets: 4 Outlets  
 Input AC Plug Type: BS 1363 (UK), Schuko (EU)  
 Communication/Configuration Ports: USB  
 Load Capacity (Watts): 360W  
 Load Capacity Volt Amp (VA): 600VA  
 Noise Level: Less than 40 dB  
 Audible Alarms: Voltage, Load Level, Battery Low, Overload  
 Category: Line Interactive  
 Recharge Time: 4-6 hours recover to 90% capacity  
 Transfer Time: Typical 2-6ms (max 10ms)  
 Waveform Type: Simulated Sine Wave  
 Backup Runtime: 5 minutes @ half load  
 Frequency Range: 50/60Hz Auto-Sensing  
 LED status light: AC Mode (Green), Battery (Flashing Yellow)  
 Surge Protection: 312 Joules  
 Visual Indicator: Touch LCD: AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault and Low Battery  
 Battery Output Voltage, Overload, Fault and Low Battery  
 Battery Volt Amp Hour Capacity: 12V/7Ah  
 Data Line Protection: RJ-11  
 AC Cord length: 1.5m



**Specifications**

See next page

**INPUT**

Acceptable Voltage Range 180 - 270 VAC

**OUTPUT**

Voltage 230 VAC

AC Voltage Regulation (Batt. Mode)  $\pm 10\%$

**BATTERY**

Battery Type & Number 12 V/7Ah x 1

**ALARM**

Battery Mode Sounds every 10 seconds

Low Battery Sounds every second

Overload Sounds every 0.5 seconds

Fault Continuously sounds

**PROTECTION**

UPS System Protection Overload, discharge, and overcharge

**ENVIRONMENT**

Humidity 0-90 % RH @ 0- 40°C (non-condensing)