

supported

DELL P Series 24 Monitor - P2423

Brand : DELL Product family: P Series Product code: P2423

Product name: Dell 24 Monitor - P2423

- 61.0cm (24") WUXGA 1920 x 1200 LED IPS
- 5ms, 16:10, 300cd/m², 1000:1
- USB, VGA, DVI, HDMI, DisplayPort

61.0cm (24") WUXGA 1920 x 1200 LED IPS, 16:10, 300cd/m², 16.7M, 5ms, 178°/178°, 1000:1

DELL P Series 24 Monitor - P2423:

See everything on our 24-inch WUXGA 16:10 monitor with versatile connectivity, a three-sided ultrathin bezel and ComfortView Plus.

DELL P Series 24 Monitor - P2423. Display diagonal: 61 cm (24"), Display resolution: $1920 \times 1200 \text{ pixels}$, HD type: WUXGA, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black











Display		Ergonomics	
Display diagonal *	61 cm (24")	VESA mounting *	✓
Display resolution *	1920 x 1200 pixels	Panel mounting interface	100 x 100 mm
HD type *	WUXGA	Cable lock slot *	✓
Native aspect ratio *	16:10	Height adjustment *	✓
Display technology *	LCD	Height adjustment	15 cm
Panel type *	IPS	Pivot	✓
Backlight type	LED	Pivot angle	90 - 90°
Touchscreen *	×	Swivelling	✓
Display brightness (typical)	300 cd/m²	Swivel angle range	-45 - 45°
Response time	5 ms	Tilt adjustment	✓
Anti-glare screen	✓	Tilt angle range	-5 - 21°
Screen shape *	Flat	On Screen Display (OSD)	1
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Plug and Play	1
Contrast ratio (typical) *	1000:1	LED indicators	√
Naximum refresh rate *	60 Hz	Power	
iewing angle, horizontal	178°	Energy efficiency class (SDR) *	D
iewing angle, vertical	178°	Energy efficiency class (HDR) *	Not available
Display number of colours *	16.7 million colours	Energy consumption (SDR) per 1000	1
Response time (fast)	8 ms	hours *	15 kWh
Pixel pitch	0.27 x 0.27 mm	Power consumption (typical) *	14.8 W
ixel density	94 ppi	Power consumption (standby) *	0.3 W
Horizontal scan range	30 - 83 kHz	Power consumption (max)	48 W
ertical scan range	56 - 76 Hz	Power consumption (off)	0.2 W
/iewable size, horizontal	51.8 cm	AC input voltage	100 - 240 V
/iewable size, vertical	32.4 cm	Input current	1.5 A
iewable size diagonal	61 cm	Power supply type	Internal
Display diagonal (metric)	60.96 cm	Energy efficiency scale	A to G
High Dynamic Range (HDR)	×		

D 11.		0	
Display		Operational conditions	
RGB colour space Colour gamut	sRGB 99%	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Performance		Operating relative humidity (H-H)	10 - 80%
NVIDIA G-SYNC * AMD FreeSync * Low Blue Light technology	×	Storage relative humidity (H-H) Operating altitude Non-operating altitude	5 - 90% 0 - 5000 m 5000 - 12192 m
Multimedia		Packaging content	
Built-in speaker(s) * Built-in camera *	×	Stand included Cables included Quick start guide	✓ AC, DisplayPort, USB, VGA ✓
Design		Weight & dimensions	
Market positioning * Product colour * Front bezel colour Detachable stand Feet colour Heavy metals free	Business Black Black Silver Hg (mercury)	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand)	531 mm 179.6 mm 510.8 mm 5.23 kg 531 mm 53.3 mm
Ports & interfaces		Height (without stand)	348.1 mm
Built-in USB hub * USB upstream port type Number of USB Type-B upstream ports quantity	✓ USB Type-B 1	Weight (without stand) Bezel width (side) Bezel width (top) Bezel width (bottom)	3.52 kg 6.3 mm 6.3 mm 1.78 cm
USB Type-A downstream ports quantity	4	Packaging data	
VGA (D-Sub) ports quantity	1	Package weight	7.71 kg
DVI port	✓	Sustainability	
DVI-I ports quantity 1 HDMI * HDMI ports quantity 1 HDMI version 1.4	√ 1	Sustainability certificates Doesn't contain European Product Registry for Energy Labelling (EPREL) code	ENERGY STAR, ROHS, TCO PVC/BFR 1043228
DisplayPorts quantity	1	Logistics data	
DisplayPort version Headphone out * AC (power) in	1.2 X	Harmonized System (HS) code	85285210
Network			
Wi-Fi	×		

