Viewsonic X2-4K data projector Standard throw projector 2150 ANSI lumens LED 2160p (3840x2160) 3D Black

Brand : Viewsonic Product code: X2-4K

Product name: X2-4K

- True 4K HDR immersive visual experience
- Advanced LED technology with 30,000 hours lifespan
- 2,900 Lumens for bright and clear images in any environment
- Easy Setup: 0.69-0.83 short throw ratio with H/V keystone & 4 corner adjustment
- Designed for Xbox for ultimate gaming experience
- Theater-level sound by Harman Kardon speakers

4K, 2900 LED Lum, 2150 ANSI, 3000000:1, 1.07 B, 1.2X, 16 GB, 6W Cube x2, Wi-fi, Bluetooth, HDMI, Audio-in/out, RS232, USB, 100-240 V, 3.6 kg

Viewsonic X2-4K. Projector brightness: 2150 ANSI lumens, Projection technology: LED, Projector native resolution: 2160p (3840x2160). Light source type: LED, Service life of light source: 30000 h. Focus: Manual, Focal length range: 10.2 - 12.25 mm, Aperture range (F-F): 2.53 - 2.73. Analog signal format system: NTSC, PAL, SECAM, Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p.

Serial interface type: RS-232, HDMI connector type: Full-size, Service port type: USB Type-A





| Projector | | Storage | |
|---|--|--|---|
| Projector brightness Smart projector * Screen size compatibility * Projection distance | # | Card reader integrated * Internal storage capacity Internal memory | X 16 GB 16 GB |
| | | Features | |
| Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Horizontal scan range Vertical scan range Keystone correction, horizontal Keystone correction, vertical | | Interactive * Noise level (economic mode) HDCP On Screen Display (OSD) On Screen Display (OSD) languages | ✓ 29 dB ✓ Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, INC, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese |
| Light source | | Number of OSD languages | 24 |
| Light source type * Service life of light source * | LED 30000 h | HDCP version Noise level * High Dynamic Range (HDR) | 1.4/2.2 33 dB |
| Lens system | | supported | ✓ |
| Focus * Focal length range Aperture range (F-F) Zoom capability | cal length range 10.2 - 12.25 mm erture range (F-F) 2.53 - 2.73 | Multimedia Built-in speaker(s) * RMS rated power Number of built-in speakers | ✓ 12 W 2 |
| Zoom type | Manual | Design | - |
| Digital zoom Optical zoom Throw ratio Vertical lens shift range Offset | ical zoom 1.2x ow ratio 0.69 - 0.83 tical lens shift range 0 - 10% | Market positioning * Product type * Product colour * Cable lock slot Cable lock slot type | Gaming Standard throw projector Black ✓ Kensington |
| Video | | Heavy metals free | Hg (mercury) |
| Analog signal format system * Full HD * 3D * | NTSC, PAL, SECAM ✓ | Display Built-in display * | × |
| Supported video modes | 480i, 480p, 576i, 576p, 720p, 1080i, | Power | |
| Ports & interfaces | 1080p, 2160p | Power source * Power consumption (typical) * | AC 236 W |
| HDMI connector type | Full-size | Power consumption (standby) * | 0.5 W |

| Ports & interfaces | | Power | |
|--|---|---|---------------------------------------|
| HDMI version Service port type USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-C ports quantity Serial interface type * PC Audio out | 2.0 USB Type-A 2 1 1 RS-232 ✓ | AC input voltage AC input frequency | 100 - 240 V 50 - 60 Hz |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 40 °C |
| | | Weight & dimensions | |
| | | Width | 355 mm |
| HDMI ports quantity * | 2 | Depth | 251 mm 121 mm |
| DVI port * X AC (power) in ✓ | × ✓ | Height Weight * | 3.6 kg |
| Network | | Package width | 490 mm |
| Ethernet LAN * Wi-Fi * Bluetooth | X X √ 4.2 | Package depth Package height Package weight | 376 mm 313 mm 5.5 kg |
| | | Packaging content | |
| | | Remote control included * Remote control type Cables included Quick start guide Warranty card | ✔ Bluetooth AC, USB Type-C ✔ |
| | | Technical details | |
| | | Image lag time | 4.2 ms |
| | | Logistics data | |
| | | Quantity per pack | 1 pc(s) |





766907019551

0766907019551

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.