

## DELL E Series 24 Monitor - E2424HS

## Brand : DELL

Product family: E Series

Product code: DELL-E2424HS

Product name : 24 Monitor -E2424HS

- 60.5cm (23.8") Full HD 1920 x 1080 LED VA
- 8ms, 16:9, 3000:1
- VGA, HDMI, DisplayPort
60.5cm (23.8") Full HD 1920 x 1080 LED VA, 16:9, 16.7M, 8ms, 178°/178°, 3000:1

## DELL E Series 24 Monitor - E2424HS:

Get outstanding value with this 23.8-inch FHD monitor featuring new three-sided narrow bezel, height adjustable stand with DP, HDMI and VGA ports.

DELL E Series 24 Monitor - E2424HS. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black








Display		Ergonomics	
Display Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time Anti-glare screen	8 ms ✓ Flat 3000:1 60 Hz 1 178° 178° 178° 16.7 million colours 5 ms 0.2745 x 0.2745 mm 93 ppi	Ergonomics         Swivel angle range         Tilt adjustment         Tilt angle range         On Screen Display (OSD)         Plug and Play         LED indicators         Power         Energy efficiency class (SDR) *         Energy efficiency class (HDR) *         Energy consumption (SDR) per 1000 hours *	-173 - 173° -5 - 21° -5 - 21° D Not available 14 kWh
Screen shape * Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density		Power consumption (typical) *16 WPower consumption (standby) *0.3 WPower consumption (max)28 WPower consumption (off)0.3 WAC input voltage100 - 24	0.3 W 28 W 0.3 W 100 - 240 V 50 - 60 Hz 1.5 A Internal
Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Display diagonal (metric) High Dynamic Range (HDR) supported RGB colour space Colour gamut	52.7 cm 29.6 cm 30 - 83 kHz 50 - 75 Hz 60.47 cm X NTSC 83%	<b>Operational conditions</b> Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m

Performance		Packaging content	
NVIDIA G-SYNC * AMD FreeSync * Flicker-free technology	× × ✓	Stand included Cables included Quick start guide	AC, HDMI
Low Blue Light technology	4	Weight & dimensions	
Multimedia Built-in speaker(s) * Built-in camera * Number of speakers RMS rated power Design Market positioning * Product colour *	✓ × 2 2 W Office Black	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	538.6 mm 209.5 mm 512.1 mm 4.06 kg 538.6 mm 48.9 mm 324.2 mm 2.82 kg
Front bezel colour Detachable stand Feet colour Heavy metals free	Black ✓ Black Hg (mercury)	Bezel width (side) Bezel width (top) Bezel width (bottom) <b>Packaging data</b>	5.8 mm 5.8 mm 2.19 cm
Ports & interfaces		Package weight	5.96 kg
Built-in USB hub * VGA (D-Sub) ports quantity HDMI * HDMI ports quantity DisplayPorts quantity	× 1 ✓ 1	Sustainability Sustainability certificates Doesn't contain European Product Registry for Energy Labelling (EPREL) code	ENERGY STAR, RoHS, TCO PVC/BFR 1294066
DisplayPort version	1.2	Carbon footprint	
Headphone out * AC (power) in	× ✓	Total carbon footprint Total carbon emissions (Standard	466 kg of CO2e 131 kg of CO2e
Network Wi-Fi Ergonomics	×	deviation) Carbon emissions (Manufacturing) Carbon emissions (Logistics)	299 kg of CO2e 27 kg of CO2e
VESA mounting *	1	Carbon emissions (Use) Carbon emissions (End-of-Life)	136 kg of CO2e 3 kg of CO2e
Panel mounting interface Cable management Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot	100 x 100 mm Kensington 13 cm	Total carbon emissions (w/o Use phase) PAIA version	330 kg of CO2e 1.3.2
Swivelling	7		



5397184657089

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.