Philips Momentum 32M1C5500VL/00 LED display 80 cm (31.5") 2560 x 1440 pixels Quad HD LCD Black

Brand : Philips

Product family: Momentum

Product code: 32M1C5500VL/00

Product name : 32M1C5500VL/00

Curved Gaming Monitor 32M1C5500VL Quad HD gaming monitor

Philips Momentum 32M1C5500VL/00 LED display 80 cm (31.5") 2560 x 1440 pixels Quad HD LCD Black:

This Philips gaming monitor delivers crystal-clear visuals and smooth gameplay. Sync technology, 165 Hz refresh rate with HDR create a lifelike experience. The slim-frame display with Ultra Wide-Color enhances visual immersion.

Philips Momentum 32M1C5500VL/00. Display diagonal: 80 cm (31.5"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black







Display Ergonomics Display diagonal * 80 cm (31.5") Cable lock slot * 1 Display resolution * 2560 x 1440 pixels Cable lock slot type Kensington Quad HD Height adjustment * HD type * × Native aspect ratio * 16:9 Tilt adjustment 1 Display technology * LCD Tilt angle range -5 - 20° VA Panel type * Simplified Chinese, Traditional Chinese, Czech, German, Dutch, W-LED Backlight type English, Spanish, Finnish, French, On Screen Display (OSD) languages Touchscreen * × Greek, Hungarian, Italian, Japanese, 250 cd/m² Display brightness (typical) Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian 4 ms Response time Plug and Play Anti-glare screen 1 LED indicators Operation, Stand-by Screen shape * Curved 1500R Screen curvature rating Power 3000:1 Contrast ratio (typical) * Energy efficiency class (SDR) * F Dynamic contrast ratio marketing Energy efficiency class (HDR) * G Mega Infinity DCR name Energy consumption (SDR) per 1000 32 kWh Maximum refresh rate * 144 Hz hours 178° Viewing angle, horizontal Energy consumption (HDR) per 57 kWh Viewing angle, vertical 178° 1000 hours Display number of colours * 16.7 million colours Power consumption (typical) * 45.1 W Power consumption (standby) * 0.5 W Response time (fast) 1 ms Pixel pitch 0.2724 x 0.2724 mm Power consumption (off) 0.3 W 100 - 240 V Pixel density 93.24 ppi AC input voltage Viewable size, horizontal 69.7 cm 50 - 60 Hz AC input frequency Viewable size, vertical 39.2 cm Internal Power supply type Display diagonal (metric) 80 cm Energy efficiency scale A to G High Dynamic Range (HDR) **Operational conditions** High Dynamic Range 10 (HDR10) technology 0 - 40 °C Operating temperature (T-T) 1 Storage temperature (T-T) -20 - 60 °C Haze rate 25% Operating relative humidity (H-H) 20 - 80% Surface hardness ЗH 0 - 3658 m Operating altitude Colour depth 8 bit

Display		Operational conditions	
RGB colour space	sRGB	Non-operating altitude	3658 - 12192 m
sRGB coverage (typical)	121.6%	Packaging content	
NTSC coverage (typical) Display sRGB	102.1%	Stand included Cables included	✓ HDMI, DisplayPort, AC
Performance		Manual	1
NVIDIA G-SYNC *	X	Weight & dimensions	
AMD FreeSync * VESA Adaptive Sync support Component video sync Flicker-free technology Low Blue Light technology Low input lag Compatible operating systems	 Separate sync Mac OS X Windows 11 / 10 / 8.1 / 8 / 7 	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	709 mm 239 mm 527 mm 7.83 kg 709 mm 95 mm 423 mm 6.37 kg
Multimedia		Packaging data	-
Built-in speaker(s) * Built-in camera *	× ×	Package width	782 mm
Design		Package depth Package height	227 mm 523 mm
Market positioning *	Gaming	Package weight	10.4 kg
Product colour * Feet colour	Black Black	Sustainability	5
Ports & interfaces		Sustainability compliance	✓
Built-in USB hub *	×	Sustainability certificates Doesn't contain	RoHS
HDMI * HDMI ports quantity	2	European Product Registry for Energy Labelling (EPREL) code	Mercury, PVC/BFR 1302102
HDMI version	2.0	Other features	
DisplayPort version1.4Audio outputHDCPHDCP version1.4		Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals	Textured SmartImage game 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
Ergonomics VESA mounting * Panel mounting interface	✔ 100 x 100 mm	EasyRead mode LowBlue mode Mean time between failures (MTBF)	4



8712581795962

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.