


10 Pack Cisco GLC-SX-MM Compatible SFP Module (10 Pack) - 1000BASE-SX - 1GbE Multimode Fiber MMF Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 550m - 850nm - DDM Cisco IE3200, IE3300, ME1200

Product ID: GLCSXMM10PST



The GLCSXMM10PST is a ten-pack of our Cisco GLC-SX-MM compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-SX compliant networks, with a maximum distance of up to 550 m (1804 ft).

Technical Specifications:

- Wavelength: 850 nm
- Maximum Data Transfer Rate: 1.25 Gbps
- Type: Multi Mode Fiber
- Connection Type: LC Connector
- Maximum Transfer Distance: 550 m (1804 ft)
- MTBF: 3,381,761 hours
- Power Consumption: Less than 1 Watt
- Digital Diagnostics Monitoring (DDM): No

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.



Certifications, Reports and Compatibility



Applications

- Replacing defective or damaged SFP modules in Cisco switches and routers
- Expand your network to remote segments

Features

• 100% CISCO GLC-SX-MM COMPATIBLE: Works with Cisco switches like IE3200, IE3300, ME1200, ME2400, N9300 and others

• TECHNICAL SPECS: 1000BASE-SX 1 Gbps Multi Mode (MMF) LC Connector 850nm Distances up to 550m (1804ft)

• TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in Cisco routers and switches; DDM support reports the transceiver's status to most SNMP network management tools

• WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules

• THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance.

Hardware		
	Warranty	Lifetime
	Compatible Brand	Cisco
	WDM	No
	Industry Standards	IEEE 802.3z 1000BASE-SX
Performance		
	Maximum Data Transfer Rate	1.25 Gbps
	Max Transfer Distance	550 m (1804 ft)
	Туре	Multi Mode





	Wavelength	850nm
	Fiber Operating Mode	Half/Full-Duplex
	DDM	No
	Compatible Networks	1000 Mbps (1 Gbps)
	MTBF	3,381,761 hours
	Power Consumption (In Watts)	< 1 W
Connector(s)	Local Unit Connectors	1 - Fiber Optic LC Duplex
Special Notes / Requirements		
	Note	For use in Gigabit fiber networking equipment and media converters
Environmental		
	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	-40C to 85C (-40F to 185F)
	Humidity	5~95% RH
Physical Characteristics		
	Product Length	2.2 in [57.0 mm]
	Product Width	0.5 in [13.0 mm]
	Product Height	0.5 in [1.2 cm]
	Weight of Product	0.6 oz [16.0 g]
Packaging Information		
	Package Length	7.1 in [18.1 cm]
	Package Width	4.9 in [12.4 cm]
	Package Height	1.4 in [36.0 mm]
	Shipping (Package) Weight	7.6 oz [214.0 g]



What's in the Box

Included in Package 10 - SFP tra

10 - SFP transceivers

*Product appearance and specifications are subject to change without notice.