

Display		Power	
Colour depth	8 bit	Power supply type	Internal
RGB colour space	sRGB	Operational conditions	
sRGB coverage (typical)	99%	Operating temperature (T-T)	0 - 40 °C
NTSC coverage (typical)	80%	Storage temperature (T-T)	-20 - 60 °C
Display sRGB	✓	Operating relative humidity (H-H)	20 - 80%
Performance		Operating altitude	0 - 3658 m
VESA Adaptive Sync support	✓	Non-operating altitude	3658 - 12192 m
Component video sync	Separate sync, Sync-on-green (SOG)	Packaging content	
Flicker-free technology	✓	Stand included	✓
Low Blue Light technology	✓	Cables included	HDMI, DisplayPort, AC
Compatible operating systems	Windows 11 / 10 / 8.1 / 8 / 7 Mac OS X	Manual	✓
Multimedia		Bundled software	SmartControl
Built-in speaker(s) *	✓	Weight & dimensions	
Built-in camera *	✗	Width (with stand)	539 mm
Number of speakers	2	Depth (with stand)	205 mm
RMS rated power	2 W	Height (with stand)	484 mm
Design		Weight (with stand)	4.85 kg
Market positioning *	Business	Width (without stand)	539 mm
Product colour *	Black	Depth (without stand)	55 mm
Front bezel colour	Black	Height (without stand)	324 mm
Feet colour	Black	Weight (without stand)	3.09 kg
Heavy metals free	Hg (mercury)	Packaging data	
Ports & interfaces		Package width	730 mm
Built-in USB hub *	✓	Package depth	139 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package height	420 mm
USB upstream port type	USB Type-B	Package weight	7.15 kg
Number of upstream ports	1	Sustainability	
Number of USB Type-B upstream ports quantity	1	Sustainability compliance	✓
USB Type-A downstream ports quantity	4	Sustainability certificates	ENERGY STAR, TCO, RoHS
USB Power Delivery	✓	Doesn't contain	Mercury, PVC/BFR
VGA (D-Sub) ports quantity	1	European Product Registry for Energy Labelling (EPREL) code	1291734
DVI port	✓	Recycling data	
DVI-D ports quantity	1	Post-consumer recycled plastic	85%
HDMI *	✓	Other features	
HDMI ports quantity	1	Exterior finish type	Textured
HDMI version	1.4	Picture enhancement	SmartImage
DisplayPorts quantity	1	Recyclable packaging material	100%
DisplayPort version	1.2	Regulatory Approvals	CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; SEMKO; TUV Ergo; TUV/GS
Audio output	✓	EasyRead mode	✓
PC Audio in	✓	LowBlue mode	✓
HDCP	✓	Mean time between failures (MTBF)	70000 h
HDCP version	1.4		



8712581796464

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-MAY-2024. Prints or copies of Information are only valid on the printed Publication date