

iiyama TE6504MIS-B3AG Signage Display Interactive flat panel 165.1 cm (65") Wi-Fi 400 cd/m² 4K Ultra HD Black Touchscreen Built-in processor iiWare 9.0

Brand : iiyama

Product code: TE6504MIS-B3AG

Product name : TE6504MIS-B3AG

iiyama TE6504MIS-B3AG. Product design: Interactive flat panel. Display diagonal: 165.1 cm (65"), Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m², HD type: 4K Ultra HD, Touchscreen. Wi-Fi. Operating system installed: iiWare 9.0. Product colour: Black



Display		Power	
Panel type	IPS	Power consumption (typical) *	173 W
LED backlighting type	Direct-LED	Power consumption (standby) *	0.5 W
Display diagonal *	165.1 cm (65")	Power consumption (off)	0.3 W
Display resolution *	3840 x 2160 pixels	AC input voltage	100 - 240 V
Display brightness *	400 cd/m ²	AC input frequency	50 - 60 Hz
HD type *	4K Ultra HD	Computer system	
Touchscreen *	✓	Built-in processor *	✓
Number of simultaneous touchpoints	20	Processor architecture	ARM Cortex-A73
Native aspect ratio	16:9	Processor cores	4
Response time	8 ms	Operating system installed	iiWare 9.0
Contrast ratio (typical)	1200:1	Weight & dimensions	
Contrast ratio (dynamic)	3500:1	Width	1488 mm
Viewing angle, horizontal	178°	Depth	86 mm
Viewing angle, vertical	178°	Height	897 mm
Display number of colours	1.07 billion colours	Weight	37 kg
Pixel pitch	0.372 x 0.372 mm	Packaging data	
Horizontal scan range	30 - 135 kHz	Package width	1628 mm
Ports & interfaces		Package depth	1005 mm
HDMI ports quantity *	3	Package height	208 mm
HDMI version	2.0	Package weight	47.6 kg
Ethernet LAN *	✓	Packaging content	
Ethernet LAN (RJ-45) ports	2	Remote control included	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Batteries included	✓
Wi-Fi *	✓	Cables included	AC, HDMI, USB
Audio		Operational conditions	
Built-in speaker(s) *	✓	Operating temperature (T-T)	0 - 40 °C
Number of built-in speakers	2	Storage temperature (T-T)	-20 - 60 °C
Design		Technical details	
Product design *	Interactive flat panel	Sustainability certificates	CE, ErP, REACH, RoHS, WEEE
Product colour *	Black	Other features	
VESA mounting *	✓	Graphics card	Mali-G52
Panel mounting interface	600 x 400 mm	User memory	32 GB

Performance		Other features	
HDCP	✓	Maximum refresh rate	60 Hz
HDCP version	2.2	Audio output	1
Mean time between failures (MTBF)	50000 h	Bluetooth	✓
		Bluetooth version	5.0
		USB 2.0 ports quantity	1



4948570120420

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAY-2024. Prints or copies of Information are only valid on the printed Publication date