

Lindy 50m Cat.6 HDMI 4K60 and IR Extender with PoC and Loop Out

Brand : Lindy Product code: 38205

Product name : 50m Cat.6 HDMI 4K60 and IR Extender with PoC and Loop Out

- Extends 4K HDMI 18G signals over 50m distances with standard network cable
- Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit, with support for HDR
- An HDMI loop-through output creates an additional viewing zone with a local display
- PoC (Power over Cable) functionality for power from a single power supply
- 2 year warranty

50m Cat.6 HDMI 4K60 and IR Extender with PoC and Loop Out


Lindy 50m Cat.6 HDMI 4K60 and IR Extender with PoC and Loop Out. Type: AV transmitter & receiver, Maximum resolution: 3840×2160 pixels, Cable types supported: Cat5e, Cat6. Connectivity technology: Wired, USB connector type: Micro-USB. Operating voltage: 24 V, Input current: 1 A. Receiver dimensions (WxDxH): $70 \times 15 \times 97$ mm, Receiver weight: 151 g, Transmitter dimensions (WxDxH): $70 \times 15 \times 97$ mm. Package width: 220 mm, Package depth: 70 mm, Package height: 130 mm







Features		Ports & interfaces	
Type *	AV transmitter & receiver	DC-in jack	✓
Maximum resolution *	3840 x 2160 pixels Cat5e, Cat6 50 m SIL9396, SIL9630	Power	
Cable types supported Maximum transfer distance Chipset		Operating voltage Input current	24 V 1 A
Maximum refresh rate	60 Hz	Operational conditions	
Extended display identification data (EDID) IR pass-through	1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 20 - 90%
HDCP pass-through	✓	Weight & dimensions	
Bandwidth	18 Gbit/s	•	
HDCP Material Product colour	Metal Black CE, FCC, REACH & California Proposition 65	Receiver dimensions (WxDxH) Receiver weight Transmitter dimensions (WxDxH) Transmitter weight	70 x 15 x 97 mm 151 g 70 x 15 x 97 mm 156 g
Certification		Packaging data	-50 g
Ports & interfaces		Packaging data Package width	220 mm
Connectivity technology * RJ-45 input ports RJ-45 output ports HDMI in	Wired 1 1 1	Package weight Package weight Package type	70 mm 130 mm 605 g Box
Number of HDMI outputs	2	Packaging content	
IDMI version 2.0 ISB ports quantity 2 ISB connector type Micro-USB	_	Cables included Manual	IR ✓
Remote (IR) input	1	Technical details	
Remote (IR) output	1	Sustainability certificates	RoHS



4002888382052

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.