PHILIPS

Philips 5000 series 49B2U5900CH/00 LED display 124 cm (48.8") 5120 x 1440 pixels Dual QHD LCD Black

Brand : Philips **Product family:** 5000 series **Product code:** 49B2U5900CH/00

Product name: 49B2U5900CH/00

Curved Business Monitor 49B2U5900CH 32:9 SuperWide curved monitor with USB-C

Philips 5000 series 49B2U5900CH/00 LED display 124 cm (48.8") 5120 x 1440 pixels Dual QHD LCD Black:

Welcome to a more efficient workspace. To facilitate everyday workflow, this monitor's large 32:9 SuperWide screen is equipped with a new busy light and tilting webcam feature that helps you flow between tasks with ease.

Philips 5000 series 49B2U5900CH/00. Display diagonal: 124 cm (48.8"), Display resolution: 5120 x 1440 pixels, HD type: Dual QHD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black











Display		Ports & interfaces	
Display diagonal *	124 cm (48.8")	Built-in KVM switch	1
Display resolution *	5120 x 1440 pixels	HDCP	1
HD type *	Dual QHD	HDCP version	1.4/2.2
Native aspect ratio *	32:9	Network	
Display technology *	LCD	Ethernet LAN	1
Panel type *	VA		•
Backlight type	W-LED	Ergonomics	
Touchscreen *	×	VESA mounting *	✓
Display brightness (typical)	450 cd/m ²	Panel mounting interface	100 x 100 mm
Response time	4 ms	Cable lock slot *	✓
Anti-glare screen	✓	Cable lock slot type	Kensington
Screen shape *	Curved	Height adjustment *	✓
Screen curvature rating	1800R	Height adjustment	15 cm
Contrast ratio (typical) *	3000:1	Swivelling	✓
Contrast ratio (dynamic)	80000000:1	Swivel angle range	-30 - 30°
Dynamic contrast ratio marketing name	SmartContrast	Tilt adjustment	√
Maximum refresh rate *	75 Hz	Tilt angle range	-5 - 15°
Viewing angle, horizontal	178°	Picture-in-Picture	√
Viewing angle, vertical	178°	On Screen Display (OSD)	V
Display number of colours *	1.07 billion colours		Simplified Chinese, Traditional Chinese, Czech, German, Dutch,
Pixel pitch	0.2328 x 0.2328 mm	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Pixel density	109 ppi		
Horizontal scan range	30 - 140 kHz		
Vertical scan range	48 - 75 Hz	Number of OSD languages	21
Viewable size, horizontal	119.2 cm	Plug and Play	<i>J</i>
Viewable size, vertical	33.5 cm	LED indicators	Operation, Stand-by
Display diagonal (metric)	124 cm		operation, ordina by
High Dynamic Range (HDR)		Power	
supported	✓	Energy efficiency class (SDR) *	F

Dicalay		Power	
Display (UDD)		Power	
High Dynamic Range (HDR) technology	DisplayHDR 400	Energy efficiency class (HDR) *	G
DDC/CI	√	Energy consumption (SDR) per 1000 hours *	43 kWh
Haze rate	25%	Energy consumption (HDR) per	02 144/6
Surface hardness	3H	1000 hours *	82 kWh
Colour depth	8 bit	Power consumption (typical) *	46.1 W
RGB colour space	sRGB	Power consumption (standby) *	0.8 W
sRGB coverage (typical)	119%	Power consumption (PowerSave)	39 W
NTSC coverage (typical)	97%	AC input voltage	100 - 240 V
Display sRGB	✓	AC input frequency	50/60 Hz
Performance		Power supply type	Internal
NVIDIA G-SYNC *	×	Energy efficiency scale	A to G
AMD FreeSync *	×	Operational conditions	
Fast charging	V	Operating temperature (T-T)	0 - 40 °C
Fast charging technology	Power Delivery	Storage temperature (T-T)	-20 - 60 °C
VESA Adaptive Sync support	✓	Operating relative humidity (H-H)	20 - 80%
Component video sync	Separate sync	Operating altitude	0 - 3658 m
Flicker-free technology	✓	Non-operating altitude	3658 - 12192 m
Low Blue Light technology	✓	Packaging content	
HBR3 support	✓	Stand included	✓
Compatible operating systems	Mac OS X Windows 11/10/8.1/8		AC, DisplayPort, HDMI, USB Type-C
Multimedia		Cables included	to USB Type-A, USB Type-C to USB
Built-in speaker(s) *	√	Manual	Type-C
Built-in camera *	·	Manual Bundled software	✓ SmartControl
Number of speakers	2		Siliarcontrol
RMS rated power	6 W	Weight & dimensions	
Megapixel (approx.)	5 MP	Width (with stand)	1193 mm
Built-in microphone	✓	Depth (with stand)	268 mm
Design		Height (with stand)	586 mm
Market positioning *	Business	Weight (with stand)	15.2 kg
Product colour *	Black	Width (without stand)	1193 mm
Front bezel colour	Black	Depth (without stand)	164 mm
Feet colour	Black	Height (without stand) Weight (without stand)	373 mm 11.6 kg
Heavy metals free	Hg (mercury)	,	11.0 kg
Ports & interfaces		Packaging data	
Built-in USB hub *	1	Package width	1290 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package depth	475 mm
USB upstream port type	USB Type-B, USB Type-C	Package height	300 mm
Number of upstream ports	2	Package weight	19.4 kg
Number of USB Type-B upstream		Sustainability	
ports quantity	1	Sustainability compliance	✓
Number of USB Type-C upstream	1		CB, CE, ENERGY STAR, EPEAT,
ports quantity	-	Sustainability certificates	Federal Communications Commission (FCC), RoHS, TCO, TUV
USB Type-A downstream ports quantity	2	Doesn't contain	Mercury, PVC/BFR
USB Type-C downstream ports			Mercury, 1 Ve, Brit
quantity	1	Recycling data	
USB Type-C DisplayPort Alternate	/	Post-consumer recycled plastic	85%
Mode		Other features	
USB Power Delivery	100 W	Picture-by-Picture (PbP)	✓
USB Power Delivery up to	100 W	Exterior finish type	Textured
HDMI *	√	Picture enhancement	SmartImage
HDMI ports quantity	2 2.0	Recyclable packaging material	100%
HDMI version	2.0		CB; CE Mark; FCC Class B; ICES-003;
DisplayPorts quantity	1.4	Regulatory Approvals	CU-EAC; EAEU RoHS; TUV Ergo;
DisplayPort version Audio output	1.4 ✓		TUV/GS; TUV Eyesafe certified; cETLus
Microphone in	4	Delta E	2
merophone III	•	EasyRead mode	✓
		LowBlue mode	✓

Other features

Philips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h

Ethernet LAN data rates 10,100,1000 Mbit/s

Wake-on-LAN ✓



8712581802578

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.