

## Brother MFC-L5710DN Laser A4 1200 x 1200 DPI 48 ppm

**Brand :** Brother

**Product code:** MFCL5710DNQJ1

**Product name :** MFC-L5710DN



A4, Electrophotographic Laser Printer, 48 pages/min, 1200x1200 dpi, LAN  
 Brother MFC-L5710DN. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 1200 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Faxing: Mono faxing. Duplex functions: Copy, Fax, Print, Scan. Maximum ISO A-series paper size: A4. Product colour: Black, White

Printing		Paper handling	
Duplex printing mode	Auto	JIS B-series sizes (B0...B9)	B5
Print technology *	Laser	Envelopes sizes	C5, Com-10, DL, Monarch
Printing *	Mono printing	Paper tray media weight	60 - 230 g/m <sup>2</sup>
Duplex printing *	✓	Ports & interfaces	
Maximum resolution *	1200 x 1200 DPI	USB port	✓
Print speed (black, normal quality, A4/US Letter) *	48 ppm	USB connector	USB Type-A / USB Type-B
Time to first page (black, normal)	6.7 s	Network	
Copying		Wi-Fi *	✗
Duplex copying *	✓	Ethernet LAN *	✓
Duplex copying mode	Auto	Cabling technology	10/100/1000Base-T(X)
Copying *	Mono copying	Security algorithms	WPA2-AES, 64-bit WEP, WPA2-PSK, 128-bit WEP, WPA2-TKIP, WPA3-SAE, WPA-AES, WPA-PSK, WPA-TKIP
Maximum copy resolution *	1200 x 600 DPI	Supported network protocols (IPv4)	ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, POP3, SMTP Client, IPP/IPPS, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMP, Web Services (Print/Scan), SNTTP Client, LDAP, IMAP4, Syslog
Time to first copy (black, normal)	8.7 s	Supported network protocols (IPv6)	NDP, RA, DNS resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, POP3, SMTP Client, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMPv6, SNTTP Client, LDAP, Web Services (Print/Scan), IMAP4, Syslog
Maximum number of copies	999 copies	Performance	
Copier resize	25 - 400%	Internal memory *	512 MB
Scanning		Sound pressure level (printing)	54 dB
Duplex scanning *	✓	Design	
Duplex scanning mode	Auto	Product colour *	Black, White
Scanning *	Colour scanning	Market positioning *	Home & office
Optical scanning resolution *	1200 x 1200 DPI	Built-in display *	✓
Scanner type *	ADF scanner	Display	TFT
Input colour depth	48 bit	Display diagonal	8.89 cm (3.5")
Output colour depth	16 bit	Control type	Touch
Input greyscale depth	16 bit	Colour display	✓
Output greyscale depth	8 bit	Power	
Scan drivers	TWAIN, WIA	Power consumption (printing)	670 W
Fax			
Duplex faxing	✓		
Faxing *	Mono faxing		
Modem speed	33.6 Kbit/s		
Fax memory	500 pages		
Auto-redialing	✓		
Features			
Duplex functions *	Copy, Fax, Print, Scan		
Number of print cartridges *	1		
Printing colours *	Black		
Page description languages	PDF, BR-Script 3, PCL 6, XPS		
Input & output capacity			
Total number of input trays *	1		
Total input capacity *	250 sheets		

<b>Input &amp; output capacity</b>		<b>Power</b>	
Total output capacity *	150 sheets	Power consumption (copying)	680 W
Auto document feeder (ADF)	✓	Power consumption (ready)	31 W
Maximum input capacity	1390 sheets	Power consumption (sleep)	5.9 W
<b>Paper handling</b>		Power consumption (off)	0.05 W
Maximum ISO A-series paper size *	A4	AC input voltage	220 - 240 V
Paper tray media types *	Bond paper, Envelopes, Labels, Letterhead, Plain paper, Postcard, Recycled paper, Thick paper, Thin paper	AC input frequency	50/60 Hz
ISO A-series sizes (A0...A9) *	A4, A5	<b>System requirements</b>	
Non-ISO print media sizes	Executive, Folio, Legal, Letter	Windows operating systems supported	Windows 10, Windows 11
		<b>Operational conditions</b>	
		Operating relative humidity (H-H)	20 - 80%
		Storage temperature (T-T)	0 - 40 °C
		Operating temperature (T-T)	10 - 32.5 °C
		Storage relative humidity (H-H)	35 - 85%
		<b>Weight &amp; dimensions</b>	
		Width	417 mm
		Depth	461 mm
		Height	448 mm
		Weight	16.6 kg
		<b>Packaging data</b>	
		Package weight	20 kg



4977766824576

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAY-2024. Prints or copies of Information are only valid on the printed Publication date