

## Samsung VM55-R Digital signage flat panel 139.7 cm (55") IPS 500 cd/m<sup>2</sup> Black 24/7

**Brand :** Samsung

**Product code:** LH55VMBRBGBXEN

**Product name :** VM55-R

55", 1920 x 1080, 500 cd/m<sup>2</sup>, 1100:1, 24/7, 16:9, 72%, AC 100 - 240 V, 50/60 Hz, 270 W, 1211.0 x 681.7 x 69.9 mm, 16800 g

Samsung VM55-R. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display technology: IPS, Display resolution: 1920 x 1080 pixels, Display brightness: 500 cd/m<sup>2</sup>. Operating hours (hours/days): 24/7. Product colour: Black



<b>Display</b>		<b>Design</b>	
Display diagonal *	139.7 cm (55")	Panel mounting interface	600 x 400 mm
Display technology *	IPS	<b>Performance</b>	
Display resolution *	1920 x 1080 pixels	Operating hours (hours/days)	24/7
Display brightness *	500 cd/m <sup>2</sup>	HDCP	✓
Native aspect ratio	16:9	International Protection (IP) code	IP5X
Contrast ratio (typical)	1100:1	HDCP version	2.2
Pixel pitch	0.63 x 0.63 mm	<b>Power</b>	
Active display area (W x H)	1209.6 x 680.3 mm	Power consumption (typical) *	165 W
Colour saturation	72%	Power consumption (sleep)	0.5 W
Haze rate	28%	Power consumption (max)	270 W
<b>Ports &amp; interfaces</b>		AC input voltage	100 - 240 V
HDMI ports quantity *	2	AC input frequency	50 - 60 Hz
HDMI version	2.0	<b>Weight &amp; dimensions</b>	
DisplayPorts quantity *	1	Width	1211 mm
USB port *	✓	Depth	69.9 mm
USB ports quantity	1	Height	681.7 mm
USB version	2.0	Weight	16.8 kg
Ethernet LAN *	✓	<b>Packaging data</b>	
Ethernet LAN (RJ-45) ports	1	Package width	1414 mm
Audio (L/R) in	1	Package depth	257 mm
Audio (L/R) out	1	Package height	844 mm
RS-232C	✓	Package weight	25.1 kg
<b>Audio</b>		<b>Packaging content</b>	
Built-in speaker(s) *	✓	Remote control included	✓
Number of built-in speakers	1	<b>Operational conditions</b>	
<b>Design</b>		Operating temperature (T-T)	0 - 40 °C
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	10 - 80%
Placement supported *	Indoor	<b>Certificates</b>	
Orientation	Horizontal/Vertical	Certification	Safety 60950-1
Product colour *	Black		
VESA mounting *	✓		



8806094282900

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAY-2024. Prints or copies of Information are only valid on the printed Publication date