Viewsonic PX704HD data projector Short throw projector 4000 ANSI lumens DMD 1080p (1920x1080) White

Brand : Viewsonic

Product name : PX704HD

Product code: PX704HD

- 1080p Full HD resolution for captivating visuals
- Unveil hidden details with a high native contrast ratio achieved through the 0.65" DMD chip
- Up to 300" screen size to maximize fun at home
- Easy multimedia access via dual HDMI ports and USB-A power supply

DLP, 1920x1080, 4000 ANSI lum, 34 dB, HDMI 1.4/ HDCP 1.4, 3.5 mm, USB-A, RS232, 100-240 V, 309x234x115 mm, 2.7 kg

Viewsonic PX704HD. Projector brightness: 4000 ANSI lumens, Projection technology: DMD, Projector native resolution: 1080p (1920x1080). Light source type: Lamp, Service life of light source: 4000 h, Service life of light source (economic mode): 15000 h. Focus: Manual, Focal length range: 10.2 - 12.24 mm, Aperture range (F-F): 2.6 - 2.78. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size

Projector

Screen size compatibility *	762 - 7620 mm (30 - 300")
Projection distance	0.9 - 2.2 m
Projector brightness *	4000 ANSI lumens
Projection technology *	DMD
Projector native resolution *	1080p (1920x1080)
Contrast ratio (typical) *	22000:1
Number of colours	1.07 billion colours
Horizontal scan range	15 - 102 kHz
Vertical scan range	23 - 120 Hz
Keystone correction, horizontal	-40 - 40°
Keystone correction, vertical	-40 - 40°
Matrix size	1.65 cm (0.65")

Light source

Light source type *	Lamp
Service life of light source *	4000 h
Service life of light source (economic mode)	15000 h
Lamp power	240 W
Lamps quantity	1 lamp(s)

Lens system

Focus *	Manual
Focal length range	10.2 - 12.24 mm
Aperture range (F-F)	2.6 - 2.78
Zoom capability	✓
Zoom ratio	2.0:1
Throw ratio	1.48-1.62
Offset	105%

Video

Analog signal format system *	NTSC, PAL, SECAM
Full HD *	✓
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200 (WUXGA)
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Ports & interfaces

HDMI connector type	Full-size
HDMI version	1.4

Network

Smart TV *	✗
Wi-Fi *	✗

Storage

Card reader integrated *	✗

Features

Interactive *	✗
Noise level (economic mode)	25 dB
HDCP	✓
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese
Number of OSD languages	20
Noise level *	34 dB

Multimedia

Built-in speaker(s) *	✓
RMS rated power	5 W

Design

Market positioning *	Presentation
Product type *	Short throw projector
Product colour *	White
Placement	Desktop, Ceiling

Display

Built-in display *	✗

Power

Power source *	AC
Power consumption (typical) *	310 W
Power consumption (standby) *	0.5 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Ports & interfaces

USB 2.0 ports quantity *	1
Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
HDMI ports quantity *	2
Composite video in *	1
DVI port *	✘
AC (power) in	✔

Weight & dimensions

Width	309 mm
Depth	234 mm
Height	115 mm
Weight *	2.7 kg
Package width	400 mm
Package depth	337 mm
Package height	168 mm
Package weight	3.8 kg

Packaging content

Remote control included *	✔
Cables included	AC, VGA
Manual	✔

Logistics data

Harmonized System (HS) code	85286200

0766907024463

766907024463