# Viewsonic LS560W data projector Standard throw projector 3000 ANSI lumens LED WXGA (1280x800) White

**Brand :** Viewsonic

**Product name :** LS560W

**Product code:** LS560W





- 3rd generation LED technology for greater sustainability
- Maintenance free: 30,000-hour light source life and less power consumption
- 3,000 ANSI Lumens offering bright images in any environment
- 0.49 short throw ratio for glare-free and shadow-free presentations
- Ease of use: instant power on/off, H/V keystone, and LAN control
3000 lum, 1280x800, DC3, 60"-300", HDMI, HDCP, USB, RS-232, 100-240V, 2.45 kg
Viewsonic LS560W. Projector brightness: 3000 ANSI lumens, Projection technology: LED, Projector native resolution: WXGA (1280x800). Light source type: LED, Service life of light source: 30000 h. Zoom type: Fixed, Offset: 110%. Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1080 (HD 1080), Supported video modes: 480i, 480p, 576i, 720p, 1080i, 1080p. Serial interface type: RJ-45, RS-232, HDMI connector type: Full-size

## Projector

| | |
|---|---|
| Supported aspect ratios | 4:3, 16:10, 16:9 |
| Screen size compatibility * | 1524 - 7620 mm (60 - 300") |
| Projection distance | 0.63 - 1.58 m |
| Projector brightness * | 3000 ANSI lumens |
| Projection technology * | LED |
| Projector native resolution * | WXGA (1280x800) |
| Contrast ratio (typical) * | 3000000:1 |
| Native aspect ratio * | 16:10 |
| Number of colours | 1.07 billion colours |
| Horizontal scan range | 15 - 102 kHz |
| Vertical scan range | 23 - 120 Hz |
| Keystone correction, horizontal | -40 - 40° |
| Keystone correction, vertical | -40 - 36° |

## Light source

| | |
|---|---|
| Light source type * | LED |
| Service life of light source * | 30000 h |

## Lens system

| | |
|---|---|
| Zoom capability | ✓ |
| Zoom type | Fixed |
| Throw ratio | 0.49 |
| Offset | 110% |

## Video

| | |
|---|---|
| Supported graphics resolutions | 640 x 480 (VGA), 1920 x 1080 (HD 1080) |
| Supported video modes | 480i, 480p, 576i, 720p, 1080i, 1080p |

## Ports & interfaces

| | |
|---|---|
| HDMI connector type | Full-size |
| HDMI version | 1.4 |
| USB 2.0 Type-A ports quantity | 1 |
| Serial interface type * | RJ-45, RS-232 |
| PC Audio in | ✓ |
| PC Audio out | ✓ |
| HDMI ports quantity * | 1 |
| DVI port * | ✗ |
| AC (power) in | ✓ |

## Network

| | |
|---|---|
| Ethernet LAN * | ✓ |
| Ethernet LAN (RJ-45) ports | 1 |
| Wi-Fi * | ✗ |

## Storage

| | |
|---|---|
| Card reader integrated * | ✗ |

## Features

| | |
|---|---|
| Interactive * | ✗ |
| Noise level (economic mode) | 26 dB |
| HDCP | ✓ |
| On Screen Display (OSD) | ✓ |
| On Screen Display (OSD) languages | Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, INC, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese |
| Number of OSD languages | 24 |
| Noise level * | 30 dB |

## Multimedia

| | |
|---|---|
| RMS rated power | 2 W |

## Design

| | |
|---|---|
| Market positioning * | Presentation |
| Product type * | Standard throw projector |
| Product colour * | White |

## Display

| | |
|---|---|
| Built-in display * | ✗ |

## Power

| | |
|---|---|
| Power source * | AC |
| Power consumption (typical) * | 157 W |
| Power consumption (standby) * | 0.5 W |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50 - 60 Hz |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |

## Weight & dimensions

| | |
|---|---|
| Width | 293 mm |

| Network | | | Weight & dimensions | |
|---|---|---|---|---|
| Smart TV * | ✖ | | Depth | 221 mm |
| | | | Height | 115 mm |
| | | | Weight * | 2.45 kg |
| | | | **Packaging content** | |
| | | | Remote control included * | ✔ |
| | | | Cables included | AC |
| | | | **Logistics data** | |
| | | | Harmonized System (HS) code | 85286200 |

0766907018103

766907018103