iiyama G-MASTER GCB3480WQSU-B1 computer monitor 86.4 cm (34") 3440 x 1440 pixels UltraWide Quad HD LCD Black

Brand: iiyama Product family: G-MASTER Product code: GCB3480WQSU-

Product name :

GCB3480WQSU-B1

iiyama G-MASTER GCB3480WQSU-B1. Display diagonal: 86.4 cm (34"), Display resolution: 3440 x 1440 pixels, HD type: UltraWide Quad HD, Display technology: LCD, Response time: 0.4 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black





Display diagonal * 344 ox 1440 pixels Display resolution * 3440 x 1440 pixels Display prost quantity 2	Display		Ports & interfaces	
FID type	Display diagonal *	86.4 cm (34")	HDMI ports quantity	2
Native aspect ratio * 21:9 HDCP ✓ Display technology* LCD Fegonomics Panel type* VA VESA mounting * ✓ Touchscreen * VA VESA mounting * ✓ Display brightness (typical) 420 c/m² Cable lock slot * ✓ Response time 0.4 ms Cable lock slot type Kensington Screen curvature rating 1500R Height adjustment * ✓ Screen curvature rating 1800 Hz Flitt angle range 20 - 5° Contrast ratio (typical) * 4000-1 Tilt angle range 20 - 5° Maximum refresh rate * 180 Hz Flitt angle range 20 - 5° Viewing angle, horizontal 178° On Screen Display (OSD) ✓ Viewing angle, horizontal scan range 48 - 180 kHz On Screen Display (OSD) languages Coech, German, Dutch, Engli Spanish, French, Italian, Japa Polish, Russian Viewable size, vertical 33.4 cm Power Energy efficiency class (SDR) * Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 kg kWh Viewable size, horizontal scan range	Display resolution *	3440 x 1440 pixels	DisplayPorts quantity	2
Display technology * VA Panel type * VA Touchscreen * X Display brightness (typical) 420 cd/m² Cable lock slot * YESA mounting	HD type *	UltraWide Quad HD	Headphone out *	✓
Panel type * VA	Native aspect ratio *	21:9	HDCP	✓
Panel type * VA	Display technology *	LCD	Ergonomics	
Touchscreen* Your Display brightness (typical) 420 cd/m² Cable lock slot *	Panel type *	VA	VESA mounting *	J
Display brightness (typical) Response time O. 4 ms Cable lock slot * Cable lock slot type Kensington Kensington Kensington Kensington Kensington Height adjustment 11 cm 12 ceth, legita djustment 11 cm 11 cm 12 ceth, legita djustment 11 cm 12 ceth, legita djustment 11 cm 12 ceth, legita djustment 11 cm 12 ceth, le			•	
Response time 0.4 ms Curved Height adjustment 4 About 11 cm About 12 cm About	Display brightness (typical)	420 cd/m²		
Screen curvature rating 1500R Height adjustment 11 cm Contrast ratio (typical) 4000:1 Tilt angle range 20 - 5° Maximum refresh rate 180 Hz Viewing angle, horizontal 178° On Screen Display (OSD) Czech, German, Dutch, Englit Pixel pitch 0.232 x 0.232 mm Horizontal scan range 48 - 180 kHz Viewable size, horizontal 79.7 cm Viewable size, horizontal 79.7 cm Viewable size, horizontal 79.7 cm Viewable size, vertical 33.4 cm Display diagonal (metric) 86.4 cm High Dynamic Range (HDR) technology High Dynamic Range (HDR) technology High Dynamic Range (HDR) technology Performance AMD FreeSync * AMD FreeSync * AMD FreeSync type AMD FreeSync refresh rate range 48 - 180 Hz AND FreeSync refresh rate range 48 - 180 Hz AND Hyper Consumption (SDR) Performance AND FreeSync refresh rate range 48 - 180 Hz AC input voltage 100 - 240 V Flicker-free technology AC input frequency 50/60 Hz Built-in camera * Weight & dimensions Width (with stand) 808 mm Destign Market positioning * Product colour * Black Certification Poscer Display (OSD) Ianguages On Screen Display (OSD) Ianguages Porture	Response time	0.4 ms		
Screen Curvature rating Contrast ratio (typical)* 4000:1 Maximum refresh rate* 180 Hz Viewing angle, horizontal Viewing angle, vertical Viewing angle, vertical Viewing angle, vertical Viewable size, horizontal Viewable size, horizontal Viewable size, vertical Display diagonal (metric) High Dynamic Range (HDR) supported Ahligh Dynamic Range (HDR) ADA FreeSync* AMD FreeSync* AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AMD FreeSync refresh rate range 48 - 180 Hz AC input voltage 100 - 240 V AC input frequency 50/60 Hz AC packaging content Weight & dimensions Width (with stand) AC pisplayPort, HDMI, USB Weight & dimensions Weight (with stand) Depth (with stand) AC preduct colour* Product colour* Black Certification Certification Product colour* Packaging data Product colour* Packaging data Packaging data Packaging data Packaging data Packaging data	Screen shape *	Curved	• •	_
Contrast ratio (typical)* 4000:1 Maximum refresh rate * 180 Hz Viewing angle, horizontal 178° Viewing angle, vertical 178° Viewing angle, vertical 178° Viewing angle, vertical 178° Number of OSD languages Viewable size, horizontal 79.7 cm Number of OSD languages 10 Power Inergy efficiency class (SDR) * E Energy consumption (SDR) per 1000 Reference on Sumption (HDR) per 1000 hours * Power consumption (typical) * AMD FreeSync * AMD FreeSync * AMD FreeSync type AMD FreeSync refresh rate range AMD FreeSync	Screen curvature rating	1500R		
Maximum refresh rate * 180 Hz Viewing angle, horizontal 178° Viewing angle, vertical 178° Viewing angle, vertical 178° Viewing angle, vertical 178° Do Screen Display (OSD) Czech, German, Dutch, Englis Spanish, French, Italian, Japa Polish, Russian Viewable size, horizontal 79.7 cm Viewable size, vertical 33.4 cm Display diagonal (metric) 86.4 cm High Dynamic Range (HDR) supported High Dynamic Range (HDR) High Dynamic Range (HDR) 400 technology Performance AMD FreeSync * AMD FreeSync type FreeSync AMD FreeSync refresh rate range 48 - 180 Hz Low Blue Light technology With technology Multimedia With technology With the thord the technology With the thendology With the	Contrast ratio (typical) *	4000:1		
Viewing angle, horizontal Viewing angle, vertical Viewing angle, vertical Viewing angle, vertical Viewable size, horizontal Viewable size, horizontal Viewable size, horizontal Viewable size, vertical Display diagonal (metric) High Dynamic Range (HDR) supported Viewable size, vertical AMD FreeSync * AMD FreeSync type AMD FreeSync teffesh rate range AB - 180 Hz Low Blue Light technology Multimedia Built-in speaker(s) * Built-in camera * Mumber of SDD languages On Screen Display (OSD) Vazech, German, Dutch, Englis Czech, Czech	Maximum refresh rate *	180 Hz		
Viewing angle, vertical Pixel pitch O.232 x 0.232 mm Horizontal scan range 48 - 180 kHz Viewable size, horizontal 79.7 cm Number of OSD languages Number of OSD languages Power Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Energy consumption (FDR) per 1000 hours * Power consumption (HDR) per 1000 hours * Power consumption (SDR) per 1000 hours * AMD FreeSync * AMD FreeSync type FreeSync tefresh rate range 48 - 180 Hz AC input voltage 100 - 240 V AC input frequency Design Multimedia Weight & dimensions Weight & dimensions Weight & dimensions Weight (with stand) Design Pockers on Son Manual Son Merce (SDR) Power consumption (FDR) Czech, German, Dutch, Englis Spanish, French, Italian, Japa Polish, Russian On Screen Display (OSD) languages 100 Spanish, French, Italian, Japa Polish, Russian On Screen Display (OSD) languages 10 22 ceth, German, Dutch, Englis Spanish, French, Italian, Japa Polish, Russian On Screen Display (OSD) languages 10 22 ceth, German, Dutch, Englis Spanish, French, Italian, Japa Polish, Russian On Screen Display (OSD) languages 10 26 chWh Energy consumption (SDR) per 1000 26 kWh Energy consumption (SDR) per 1000 26 kWh High Dynamic Range (HDR) 40 hours * Power consumption (HDR) per 1000 hours * Power consumption (EDR) per 1000 26 kWh FreeSync type F	Viewing angle, horizontal	178°		
Pixel pitch 0.232 x 0.232 mm	Viewing angle, vertical	178°	on sereen bisplay (65b)	•
Viewable size, vertical Display diagonal (metric) High Dynamic Range (HDR) supported High Dynamic Range (HDR) supported High Dynamic Range (HDR) High Dynamic Range (HDR) technology Performance AMD FreeSync * AMD FreeSync type AMD FreeSync refresh rate range Flicker-free technology AW Hash Hash Built-in speaker(s) * Built-in speaker(s) * Built-in camera * Number of speakers Number of speakers RMS rated power Design Market positioning * Office Product colour * Market positioning * Or A certain and support, Erp, WEEE, Packaging data Energy consumption (SDR) per 1000 26 kWh Energy consumption (HDR) 26 kWh Energy consumption (HDR) 26 kWh Energy consumption (HDR) 26 kWh Energy consum			On Screen Display (OSD) languages	Spanish, French, Italian, Japanese,
Display diagonal (metric) High Dynamic Range (HDR) supported High Dynamic Range (HDR) High Cynsumption (SDR) per 100 26 kWh hours For kwh Dewer consumption (HDR) per 100 As U As Input voltage As C Input frequency As Input fr	Viewable size, horizontal	79.7 cm	Number of OSD languages	10
High Dynamic Range (HDR) supported	Viewable size, vertical	33.4 cm	Power	
High Dynamic Range (HDR) supported High Dynamic Range (HDR) High Dynamic Range (HDR) 400 Energy consumption (BDR) per 1000 hours * FreeSync FreeSync Power consumption (typical) * AMD FreeSync type FreeSync Power consumption (off) 0.3 W AMD FreeSync refresh rate range 48 - 180 Hz AC input voltage 100 - 240 V Flicker-free technology AC input frequency 50/60 Hz Low Blue Light technology AC input frequency 50/60 Hz Built-in speaker(s) * Built-in camera * Number of speakers 2 RMS rated power 6 W Design Width (with stand) 808 mm Design Weight (with stand) 551.5 mm Market positioning * Office Weight (with stand) 7.6 kg Packaging data Certification CE, EAC, RoHS support, ErP, WEEE, Pockago width 8 por packaging data Packaging data Packaging data Packaging data Packaging width 8 por packaging data Packaging data Packaging width 8 por packaging data Packaging data Packaging data Packaging data Packaging data Packaging width 8 packaging data Packaging data Packaging data Packaging data Packaging width 8 packaging data Packaging data Packaging data Packaging data Packaging width 8 packaging data Packaging data Packaging data Packaging width 8 packaging widt	Display diagonal (metric)	86.4 cm	Energy efficiency class (SDR) *	F
High Dynamic Range (HDR) technology High Dynamic Range (HDR) 400 Performance AMD FreeSync * AMD FreeSync type FreeSync AMD FreeSync refresh rate range Blue Light technology Multimedia Built-in speaker(s) * Built-in camera * Number of speakers Number of speakers RMS rated power Design Market positioning * Power consumption (HDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * O.5 W AC input voltage 100 - 240 V 50/60 Hz AC input frequency 50/60 Hz AC DisplayPort, HDMI, USB AC DisplayPort, HDMI, USB Weight & dimensions Width (with stand) Depth (with stand) To Ackaging data Packaging width		1	Energy consumption (SDR) per 1000	
Performance AMD FreeSync * ✓ ✓ Power consumption (typical) * 0.5 W AMD FreeSync type FreeSync Power consumption (off) 0.3 W AMD FreeSync refresh rate range 48 - 180 Hz AC input voltage 100 - 240 V Flicker-free technology ✓ AC input frequency 50/60 Hz Low Blue Light technology ✓ Packaging content Multimedia Cables included AC, DisplayPort, HDMI, USB Built-in speaker(s) * ✓ Quick start guide ✓ Weight & dimensions Number of speakers 2 RMS rated power 6 W Design Height (with stand) 256 mm Market positioning * Office Weight (with stand) 551.5 mm Market positioning * Office Weight (with stand) 7.6 kg Product colour * Black Certification CE, EAC, RoHS support, ErP, WEEE, Certification CE, EAC, RoHS support, ErP, WEEE, Power consumption (typical) * 0.5 W Ones on sumption (typical) * 0.5 W Ones of the consumption (off) Ones of		High Dynamic Range (HDR) 400	Energy consumption (HDR) per	57 kWh
AMD FreeSync *	Performance			51 W
AMD FreeSync type FreeSync Power consumption (off) 0.3 W AMD FreeSync refresh rate range 48 - 180 Hz AC input voltage 100 - 240 V Flicker-free technology AC input frequency 50/60 Hz Low Blue Light technology Packaging content Multimedia Cables included AC, DisplayPort, HDMI, USB Built-in speaker(s) * Quick start guide Weight & dimensions Number of speakers 2 RMS rated power 6 W Design Width (with stand) 808 mm Depth (with stand) 256 mm Depth (with stand) 551.5 mm Market positioning * Office Weight (with stand) 7.6 kg Product colour * Black Certification CE, EAC, RoHS support, ErP, WEEE, Certification Packaging data	AMD FreeSync *	✓	• • •	0.5 W
AMD FreeSync refresh rate range	•	FreeSync	•	0.3 W
Flicker-free technology Low Blue Light technology Multimedia Built-in speaker(s) * Built-in camera * Number of speakers RMS rated power Design Market positioning * Poffice Product colour * Black Certification AC input frequency AC input frequency Sol/60 Hz AC, DisplayPort, HDMI, USB AC, DisplayPort, HDMI, USB AC, DisplayPort, HDMI, USB Weight & dimensions Width (with stand) Book mm Depth (with stand) Sol/60 Hz AC input frequency Sol/60 Hz AC, DisplayPort, HDMI, USB Weight & dimensions Width (with stand) Book mm Depth (with stand) Sol/60 Hz AC input frequency AC input frequency Weight & dimensions Width (with stand) Sol 8 mm Depth (with stand) Sol 9 mm Sol 9 mm		•	• • •	100 - 240 V
Multimedia Cables included AC, DisplayPort, HDMI, USB Built-in speaker(s) * Built-in camera * Number of speakers Number of speakers RMS rated power Design Market positioning * Office Product colour * Black Certification Cables included AC, DisplayPort, HDMI, USB Weight & dimensions Width (with stand) 808 mm Depth (with stand) 256 mm Height (with stand) 551.5 mm 7.6 kg Packaging data Certification Certification Cables included AC, DisplayPort, HDMI, USB AC, DisplayPort, HDMI, USB Weight & dimensions Width (with stand) 808 mm Depth (with stand) 7.6 kg Packaging data		✓	AC input frequency	50/60 Hz
Multimedia Cables included AC, DisplayPort, HDMI, USB Built-in speaker(s) * ✓ Quick start guide ✓ Built-in camera * X Weight & dimensions Number of speakers 2 Width (with stand) 808 mm Pestign Depth (with stand) 256 mm Height (with stand) 551.5 mm Market positioning * Office Weight (with stand) 7.6 kg Product colour * Black Packaging data Certification CE, EAC, RoHS support, ErP, WEEE, Package width 890 mm		✓	Packaging content	
Built-in camera * Number of speakers RMS rated power Pesign Market positioning * Product colour * Certification Packaging data Weight & dimensions Width (with stand) Bush m Depth (with stand) Pepth (with stand) Speckaging data Packaging data Speckage width Packaging width Packa	Multimedia			AC, DisplayPort, HDMI, USB
Number of speakers RMS rated power 6 W Design Design Market positioning * Product colour * Black Certification Certification Width (with stand) Depth (with stand) Weight (with stand) Solvential (with stand) Weight (with stand) To ke Packaging data Solvential (with stand) Packaging data Solvential (with stand) Packaging data	Built-in speaker(s) *	✓	Quick start guide	• •
Number of speakers RMS rated power 6 W Depth (with stand) Depth (with stand) Depth (with stand) Solution 1 Depth (with stand) Froduct colour * Depth (with stand) Weight (with stand) Weight (with stand) To kg Packaging data Certification Package width Package w	Built-in camera *	X	Weight & dimensions	
RMS rated power 6 W Depth (with stand) 551.5 mm Market positioning * Product colour * Black Certification Certification 6 W Depth (with stand) Weight (with stand) 7.6 kg Packaging data Packaging data	Number of speakers	2	•	808 mm
Design Height (with stand) 551.5 mm Market positioning * Office Weight (with stand) 7.6 kg Product colour * Black Packaging data Certification CE, EAC, RoHS support, ErP, WEEE, Package width 899 mm	RMS rated power	6 W	,	
Market positioning * Office Weight (with stand) 7.6 kg Product colour * Black Certification CE, EAC, RoHS support, ErP, WEEE, Packaging data Packaging width 800 mm	Design		·	
Product colour * Black Packaging data Certification CE, EAC, RoHS support, ErP, WEEE, Package width Separate	y	Office		
Certification CE, EAC, RoHS support, ErP, WEEE,		Black		7.0 kg
(errification Packago width 900 mm			Packaging data	
REACH, UKCA	Certification		Package width	899 mm
Package depth 237 mm			Package depth	237 mm

Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Package height	502 mm
USB hub version HDMI *	3.2 Gen 1 (3.1 Gen 1)	Package weight	10.6 kg
	✓	Sustainability	
		European Product Registry for Energy Labelling (EPREL) code	1654168



4948570122257

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.