

Combo Kit LXT® DLX2412TJ

Includes DHP486Z 18V Brushless Combi Drill, DTD154Z 18V Brushless Impact Driver



Models in kit



**Combi Drill LXT®
DHP486**



**Impact Driver LXT®
DTD154**

Combi Drill LXT®

DHP486

18V • 130 Nm • 0 – 2 100 min⁻¹

A powerful, brushless general-use impact drill for screwdriving and drilling

An efficient, brushless drill for screwdriving and drilling with or without hammer action, two power settings. Max. torque of 130 / 65 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.



LXT **BL** MOTOR 18V

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
No load speed	0 - 550 / 2100 min ⁻¹
Max. fastening torque Hard/Soft	130 / 65 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 8250 / 31 500 min ⁻¹
Max. Drilling Diameter in Wood	76 mm
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- Optimum handle design
- LED light illuminates the work site
- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device

[Link to product - www.makita.com](http://www.makita.com)



Impact Driver LXT®

DTD154

18V • 1/4" • 175 Nm • 0 – 3 600 min⁻¹

Extra-compact brushless impact driver with three power settings for quick driving

A compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 175 Nm. Three power settings, suitable for quick driving. Handy LED light.



LXT **BL** **18V**
MOTOR

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
No load speed	0 - 1100 / 2100 / 3600 min ⁻¹
Max Fastening Torque Impact Drill	175 Nm
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1100 / 2600 / 3800 min ⁻¹
Sound Power Level (L _{WA})	107 dB(A)
Sound Pressure Level (L _{pA})	96 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	12,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²

User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Related products kit

Standard AC

122576-8
Stopper Pole



122D10-2
Grip Assembly



251314-2 (2x)
Truss Head Screw M4*12, Td140D



266622-8
Truss Head Screw M4 X 12



346317-0 (2x)
Belt Hook



452947-8
Bitholder



784637-8 (2x)
Screw Bit, Ph2 – S6, 45 Mm, Double



821551-8
Makpac case (3)



Standard MA

DC18RC
Battery Charger LXT®



BL1850B (2x)
Battery LXT® 5,0 Ah



Optional AC

122576-8
Stopper Pole



821551-8
Makpac case (3)



122D10-2
Grip Assembly



821550-0
Makpac case (2)



837916-4
MakPac (2) Inlay



BL1820B
Battery LXT® 2,0 Ah



BL1830B
Battery LXT® 3,0 Ah



BL1840B
Battery LXT® 4,0 Ah



BL1850B
Battery LXT® 5,0 Ah



BL1860B
Battery LXT® 6,0 Ah



Other - DHP486

[User manual](#)

[Parts drawing](#)

 **Other - DTD154**

User manual

Parts drawing