

65" 4K UHD Interactive Touchscreen featuring hybrid Android or Slot PC capabilities for every space.

Inspiring immersive collaboration for education and enterprise, the TE6514MIS-B1AG from iiyama is a hybrid interactive solution, allowing you to smoothly annotate in 4K and control any content on the display from any source.

This PureTouch-IR+ 50-point Touchscreen with iiWare 11 (Android 13 OS) features Note, Browser, Cloud Drive and the option for you to sideload relevant apps. Incorporating additional USB-C connections, the display supports the latest in video, audio and Touch signal via a single port and it allows you to charge your device with 100W power delivery. You can be sure that no matter what your Interactive aspiration, iiyama has the simplified solution just for you.

Boasting a new Android 4K Interface (iiWare 11) with User Profiles for simple login and access to your very own bespoke menu and Cloud Drives, this 65" Touchscreen becomes a highly personalised device. Benefit from the flexibility and clarity that the 65" VA panel offers, providing vibrant, detailed and high-quality images from anywhere in the class or meeting room. The anti-glare coating drastically reduces ambient reflection in high-brightness environments without compromising the sharpness and clarity of the image.

The high quality built-in 8-Array Microphone and powerful Dual Directional Speakers support conferencing configurations and our 500Hz Frame Rate Touch sensor delivers the smoothest and fastest Touch response ever seen with added Touch features like Dual Palm Rejection and Anti-Bacterial Pens for safety in multiple user environments. Easily save your notes and on-screen content directly to a USB device, 64GB internal memory or a selected cloud drive.

The new Multi-Screen Display feature allows you to link multiple screens and run as many different applications as you need for dual and triple display integration in large spaces like lecture amphitheatres and large meeting/boardrooms.

Share, stream and edit content from any device directly on screen and Vice Versa to transform your team meetings or lessons into an easy, fast and seamless interactive session with the included WiFi module ([OWM002](#)) utilising the iiyama Share or EShare app.



PureTouch-IR+

PureTouch-IR+ from iiyama delivers 1mm touch accuracy for the smoothest and fastest annotation. Enjoy precise and responsive 50pt Touch technology with Touch pen recognition.



iiWare 11

iiWare 11 features Note, Browser, Cloud Drive and the option for you to sideload relevant apps you require for your organisation. These collaborative tools and hybrid solution deck of Android 13 empowers all education, training and presentation environments to seamlessly deliver engaging content.

01 DISPLAY CHARACTERISTICS

Design	Thin bezel
Diagonal	65", 163.9cm
Panel	VA, haze 25%
Touch Glass	Anti-Gloss treatment, Anti-Glare glass, Matt polished surface, Ultra smooth writing, Zero Air-Gap
Native resolution	3840 x 2160 (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	435 cd/m ²
Light transmittance	92%
Static contrast	4000:1
Dynamic contrast	5000:1
Response time (GTG)	6.5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (NTSC 72%)
Horizontal Sync	30 - 135kHz
Viewable area W x H	1429 x 804mm, 56.3 x 31.7"
Bezel width (sides, top, bottom)	16.5mm, 16.5mm, 41mm
Pixel pitch	0.372mm
Bezel colour and finish	black, matte

02 TOUCH

Touch technology	PureTouch-IR ⁺
Touch points	50, 10pt writing (HID, only with supported OS)
Touch accuracy	+/- 1mm
Touch method	stylus, finger, glove (Passive pen, Opaque objects)
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Palm rejection	yes

03 INTERFACES / CONNECTORS / CONTROLS

Digital signal input	HDMI x4 (2.0, max. 3840x2160 @60Hz, YUV420/ YUV444/ RGB444) DisplayPort x1 (2.1, max. 3840x2160 @30Hz) USB-C x2 (3.1, 3840x2160 @60Hz, RGB444 DP 1.2 Alt mode, Touch, 1x front: 100W PD, 1x back: 15W PD)
Audio input	Mini jack x1
Monitor control input	RS-232c x1 (DSUB 9pin) RJ45 (LAN) x1 (LAN Control) IR x1
Digital signal output	HDMI x1 (2.0, max. 3840x2160 @60Hz, MSD (Multi-Screen Display)) USB-C x1 (3.1, 3840x2160 @60Hz (DP 1.2 Alt mode, Touch, 5W PD, MSD (Multi-Screen Display))
Audio output	S/PDIF (Optical) x1 Mini jack x1 Speakers 2 x 18W (Facing up), 2x 8W (Front facing)
HDCP	HDMI: 2.3 + 1.4, DP: 2.3 + 1.3 USB-C: 2.3 + 1.3
USB ports	x6
RJ45 (LAN)	x2 (Auto switch for PC & Android, 1000MB)

Microphone 8-Array (8m voice pick-up, Front facing)

04 FEATURES

Integrated software iiWare 11 (Android 13 OS) featuring iiyama DMS, Note, web browser, file manager, cloud drives, WPS office, iiyama Share and EShare for wireless connection with Windows/iOS/Android devices.

WiFi yes (WiFi Module OWM002 - Dual WiFi Bandwidth: 2.4GHz/5GHz, WiFi Standard: IEEE 802.11 a/b/g/n/ac, Bluetooth Support: 2.1/3.0/4.2/5.0)

Hardware CPU: Quad core A76+A55, GPU: Mali G610 MC4, RAM: 8GB, ROM: 64GB

Extra WiFi Module (OWM002), Slot for optional OPS Slot PC, 4x Touch pen

Kiosk mode yes

Max. non-stop operating time 24/7

Media playback yes

Glass thickness 3mm

Glass hardness 7H

Housing (bezel) metal

OSD key lock yes

05 GENERAL

OSD languages EN, DE, FR, ES, IT, RU, CZ, NL, PL, CAT, SV, FI, DA, NB

Control buttons Power button, Power Indicator, Remote Sensor, Light Sensor, USB-C Connector (3.1)

User controls general settings (input, volume, backlight), audio settings (volume, bass, treble, balance, sound mode, mute), screen settings (pixel shift, eye care, auto light, ECO, ECR), display settings (brightness, contrast, hue, sharpness, display mode, colour temp.), settings (wireless & networks, personal, input & output, application, system, administrator, about)

Blue light reducer yes

Plug&Play DDC2B

Warranty 5 years (for details and eligible countries please check the Warranty section of our website)

06 MECHANICAL

Orientation landscape

Fanless design yes

VESA mounting 600 x 400mm

Operation temperature range 0°C - 40°C

Storage temperature range - 20°C - 60°C

MTBF 50.000 hours (excluding backlight)

07 ACCESSORIES INCLUDED

Cables power, USB, HDMI

Touch pen x4 (Dual function tips, Anti-bacterial)

Guides quick start guide, safety guide

Other WiFi Module (OWM002), Mounting bracket for NUC, Mounting bracket for webcam

Remote control yes (batteries included)

08 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	150W typical, 0.5W stand by, 0.3W off mode

09 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH (RoHS)
REACH SVHC	above 0.1%: Lead

10 DIMENSIONS / WEIGHT

Product dimensions W x H x D	1488 x 908 x 86mm
Box dimensions W x H x D	1628 x 1005 x 208mm
Weight (without box)	39kg
Weight (with box)	48.3kg
EAN code	4948570122028



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED