



TP-Link UB5A network card Bluetooth

Brand : TP-Link

Product code: UB5A

Product name : UB5A

- Bluetooth 5.0 – Applies the latest Bluetooth 5.0 technology, backward compatible with Bluetooth V4.0/3.0/2.1/2.0/1.1
 - Wireless Connectivity – Provides stable and convenient communication between Bluetooth devices and your PC or laptop
 - Nano-Sized – Ultra-small for convenient portability with reliable high performance
 - Supported Operating System – Windows 10/8.1/7
- Bluetooth 5.0, USB 2.0, 14.8 × 6.8 × 18.9 mm
TP-Link UB5A. Connectivity technology: Wireless, Host interface: USB, Interface: Bluetooth



Ports & interfaces		Operational conditions	
Connectivity technology *	Wireless	Storage relative humidity (H-H)	5 - 90%
Host interface *	USB	Sustainability	
Interface *	Bluetooth	Sustainability compliance	✓
USB version	2.0	Sustainability certificates	CE, Federal Communications Commission (FCC)
Network		Weight & dimensions	
Bluetooth	✓	Width	14.8 mm
Bluetooth version	5.0	Depth	6.8 mm
Design		Height	18.9 mm
Component for *	PC	Packaging data	
Internal *	✗	Package width	118 mm
		Package depth	102 mm
		Package height	23 mm
		Package weight	30 g
		Packaging content	
		Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	85176990

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
-------------------------------------	---

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%



4897098687802

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAY-2024. Prints or copies of Information are only valid on the printed Publication date