

## ZW350e Ultra-compact high brightness laser projector





- Bright WXGA laser projector 4000 lumens and IP6X certified
- Designed with the environment in mind -DuraCore laser technology cuts power consumption and ensures a long product lifespan
- Ultra compact for easy installation 1.1x zoom, 360-degree and portrait projection
- Excellent image quality Perfect for meeting rooms, medium-sized exhibition venues, events or tradeshows



The ZW350e is Optoma's most compact, hassle free WXGA DuraCore laser projector to date. This 4000-lumen projector is built for maintenance-free continuous operation up to 30,000 hours, while its small and lightweight footprint makes it 34% smaller than any other projector in the Optoma range, offering flexible installation in virtually any orientation and location.

## **Specifications**

EAN: 5055387666382, Colour: White	9
Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	4,000 lumens
Contrast ratio	300,000:1
lative aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
las vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
lorizontal scan rate	15 ~ 140Khz
/ertical scan rate	24 ~ 120Hz
Jniformity	75%
Screen size	0.51m ~ 7.62m (20" ~ 300") diagonal
amp info	
.ight source type	Laser
ASER life	30,000 hours
Optical	
hrow ratio	1.54:1 ~ 1.72:1
Projection distance (m)	1m - 10m
loom	1.1
Zoom type	Manual
ocal length (mm)	21.85 ~ 24.00
lative offset	112%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
General	
loise level (typical)	31dB
loise level (max)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
D companying	SECAM B,D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz)
BD	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
P rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m
Remote control	Card style
Speaker count	1
•	
Vatts per speaker	15W
n the box	AC power cord
	Remote control 2x AAA batteries
	ZX AAA batteries Basic user manual
Optional wireless models	
	UHDCast Pro
ower	
ower supply	100V ~ 240V, 50-60Hz
	<0.5W
Power consumption (standby)	88W
	0000
Power consumption (min)	139W
Power consumption (min) Power consumption (max)	
Power consumption (min) Power consumption (max) Neight and dimensions	139W
Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm	139W 274 x 216 x 114
Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm Gross weight Net weight	139W







Copyright © 2022, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 21122022034620