

ZH450

Eco-friendly ultra-compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -4500 lumens and IP6X certified
- Small form factor for easy installation 1.6x zoom, 360-degree and portrait projection
- DuraCore laser technology Long laser life span of up to 30,000 hours maintenance-free operation
- Built with the environment in mind Made with non-hazardous and recycled materials



The ZH450 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

Specifications

EAN: 5055387666825, Colour: White

UPC: 796435 44 659 8, Colour: White

Display/image

Display technology DLP™

Resolution 1080p Full HD (1920x1080)

Brightness 4.500 lumens Contrast ratio 300,000:1 2,000,000:1 Contrast ratio - dynamic 16:9 Native aspect ratio 4:3 16:9 Aspect ratio - compatible Keystone correction -+/-30°

Keystone correction - vertical +/-30° Has vertical auto keystone Yes

correction

horizontal

Displayable colours (millions) 1073.4 Horizontal scan rate 15 ~ 140Khz 24 ~ 120Hz Vertical scan rate Uniformity 75%

0.51m ~ 8.18m (20" ~ 322") diagonal Screen size

Lamp info Light source type LASER life Optical

30,000 hours

1.4:1 ~ 2.24:1 Throw ratio Projection distance (m) 1m - 10m 1.6 Zoom type Manual Focal length (mm) 20.91 ~ 32.62

116%

Native offset Connectivity

Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General Noise level (typical) Noise level (max)

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

29dB

31dB

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r

3D compatibility

3D 3D ready

Security Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Operating conditions

Remote control Card style Speaker count 15W Watts per speaker In the box AC power cord

Remote control 2x AAA batteries Basic user manual

Optional wireless models UHDCast Pro

Power

Power supply 100V ~ 240V, 50-60Hz

Power consumption (standby) <0.5W Power consumption (min) 119W Power consumption (max) 173W

Weight and dimensions

Dimensions (W x D x H) mm 274 x 216 x 114 4.2 kg Gross weight Net weight 3 kg



