



Versatile Portable Projector with High Brightness

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 4200 ANSI lumens of brightness and 30,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA (1280 x 800) native resolution scalable up to a maximum WUXGA (1920 x 1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Auto vertical keystone
- Diverse connectivity, HDMI v1.4, USB-A power
- Compact and lightweight at 4.8kg for easy portability
- 3D ready and support various forms
- A long life up to 30,000 hrs. (Eco Mode) for low Total Cost of Ownership (TCO)
- Audio ready with built-in 10 watt audio speaker, audio-in and audio-out ports
- Smart Control: quick cooling, instant restart, auto power off, reminder message, security settings, 0.5W in standby mode and more...
- Environmentally friendly design and compliance



From meeting room to presentations anywhere on the road

The DW2650Z is a native WXGA projector that integrates advanced DLP® and BrilliantColor™ technologies, delivering striking, vibrant images in a widescreen format. It provides an array of connectivity options, including two HDMI v1.4 ports, and boasts a brightness level of 4,200 ANSI Lumens with a remarkable 30,000:1 contrast ratio. Its lightweight and compact design facilitates effortless installation that will fit any budget.



DW2650Z SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	4200 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1,920 x 1,200)
	Contrast Ratio	30,000:1
	Automatic Keystone Correction	Automatic Keystone Correction
	Native Aspect Ratio	16:10
	Keystone Correction	Vertical ±30°
Optical	Throw Ratio	1.544~1.860
	Image Size (Diagonal)	40" - 300"
	Projection Distance	1.31 - 10.21m
	Projection Lens	F = 2.42 - 2.62, f = 22 - 25.79mm
	Zoom Ratio	1.2x
	Offset	104%±5% (Full Height)
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Compatibility	Video	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI Number of Ports 1.4 (2), Audio-In (RCA) , Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS-232, USB A (2.0 (Power 5V/1.5A)), USB miniB (Service)
General	Lamp Life and Type	20,000 / 30,000 hours (Normal / Eco)
	Speakers	10W (Mono)
	Dimensions (W x D x H)	353 x 290 x 144mm
	Weight	4.8 kg
	Noise Level	33dB/31dB (Normal/Eco Mode)
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Normal Mode), 180W (Eco Mode), <0.5W (Standby)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first, Laser Phosphor Warranty: 3-Year warranty on projector/ 3-year or 10000h on the Laser Phosphor illumination source. (Whichever comes first)
	Standard Accessories	VGA Cable, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Remote Control P/N (XX5040005400)
	UPC Code	813097025661