Product data sheet Characteristics

APCRBC143

APC Replacement Battery Cartridge #143



Overview

Model Name	APC Replacement Battery Cartridge #143	
Includes	All required connectors , Battery recycling guide , Installation guide , Reusable packaging	
Standard Lead Time	Usually in Stock	
Product Distribution	Albania , Andorra , Australia , Austria , Belgium , Bosnia And Herzegovina , Bulgaria , Cambodia , Canada , Croatia , Cyprus , Czech Republic , Denmark , Estonia , Finland , France , Germany , Gibraltar , Greece , Hungary , Iceland , Indonesia , Ireland , Italy , Latvia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malaysia , Malta , Moldova, Republic Of , Myanmar , Nepal , Netherlands , New Zealand , Norway , Philippines , Poland , Portugal , Romania , Russian Federation , Singapore , Slovakia (Slovak Republic) , Slovenia , Spain , Sweden , Switzerland , Thailand , Ukraine , United States , Viet Nam	

Output

Battery Output Voltage	120
------------------------	-----

Batteries & Runtime

Battery Volt-Amp-Hour Capacity	600
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte: leakproof
Battery mounting	Enclosed battery cartridge
Battery mounting	3 - 5
RBC Quantity	1
Battery blocks per string	10

Physical

Model Name APC Replacement Battery Cartridge #143		
Includes	All required connectors , Battery recycling guide , Installation guide , Reusable packaging	
Standard Lead Time	Usually in Stock	
Product Distribution	Albania , Andorra , Australia , Austria , Belgium , Bosnia And Herzegovina , Bulgaria , Cambodia , Canada , Croatia , Cyprus , Czech Republic , Denmark , Estonia , Finland , France , Germany , Gibraltar , Greece , Hungary , Iceland , Indonesia , Ireland , Italy , Latvia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malaysia , Malta , Moldova, Republic Of , Myanmar , Nepal , Netherlands , New Zealand , Norway , Philippines , Poland , Portugal , Romania , Russian Federation , Singapore , Slovakia (Slovak Republic) , Slovenia , Spain , Sweden , Switzerland , Thailand , Ukraine , United States , Viet Nam	
Output		
Battery Output Voltage	120	
Batteries & Runtime		
Battery Volt-Amp-Hour Capacity	600	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Battery mounting	Enclosed battery cartridge	
Battery mounting	3 - 5	
RBC Quantity	1	
Battery blocks per string	10	
Physical		
Net Weight	22.27 kg	
Maximum Height	225.0 mm	
Maximum Width	279.0 mm	
Maximum Depth	481.0 mm	
Shipping Weight	25.18 kg	
Shipping Width	293.0 mm	
Shipping Height	253.0 mm	
Shipping Depth	495.0 mm	
Units per Pallet	32.0	

Environmental

Storage Relative Humidity	0 - 95 %
Storage Temperature	-15 - 45 °C
Operating Elevation	0-3000 meters
Operating Relative Humidity	0 - 95 %
Operating Environment	0 - 40 °C

Conformance

Standard warranty	1 year repair or replace	
-------------------	--------------------------	--

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs