

Travel A/V Adapter: 2-in-1 Mini DisplayPort to HDMI or VGA Converter

Product ID: MDP2HDVGA



This travel adapter lets you connect your mDP enabled Ultrabook™ or laptop computer to any VGA or HDMI® display. The 2-in-1 Mini DisplayPort adapter is the perfect accessory for any of your Microsoft® Surface™ Pro devices equipped with mDP.

Connect to any HDMI or VGA display

Why carry multiple adapters when you only need one? Instead of keeping two different adapters on-hand, the MDP2HDVGA mDP travel adapter offers both VGA and HDMI outputs, so you'll be able to connect from your laptop mDP output to any modern boardroom or classroom display -- an ideal plug-and-play solution for BYOD (Bring Your Own Device) applications at the office.

Plus, because the converter supports video resolutions up to 1920x1200 or 1080p you can convert a Mini DisplayPort video source to HDMI or VGA without sacrificing video quality.







Maximize portability

The travel A/V adapter maximizes portability with a small footprint and lightweight design. The convenient design ensures the adapter is as portable as your laptop, fitting easily into your laptop bag or carrying case and eliminates the need to carry more than one adapter. With this adapter you can walk into virtually any boardroom ready to present, making a great first impression, and saving you the embarrassment of having to rummage through your bag looking for the right connector.

The 2-in-1 converter is compatible with the Intel Thunderbolt port on your computer and installs easily with no software or drivers required.

The MDP2HDVGA is backed by a 3-year StarTech.com warranty and free lifetime technical support.





Data Sheet

Certifications, Reports and Compatibility









Applications

- Keep the adapter with you while traveling, to connect to virtually any display you come across
- Connect your BYOD laptop/Ultrabook to a provided HDMI, or VGA display at work
- Connect a VGA, or HDMI display to your Mini DisplayPort laptop, to use as a secondary monitor

Features

- 2-in-1 design lets you connect your mDP computer to any HDMI or VGA display using a single adapter
- Maximize portability with a compact, lightweight adapter you can easily carry in your laptop bag
- Supports video resolutions up to 1920x1200 or 1080p
- Compatible with Intel Thunderbolt
- Plug-and-play installation
- No power adapter required



Data Sheet

	Warranty	3 Years
Hardware	Active or Passive Adapter	Active
		Passive
	Adapter Style	Adapters
	Audio	Yes
	AV Input	Mini-DisplayPort
	AV Output	HDMI
		VGA
Performance	Audio Specifications	5.1 Surround Sound (Video source and destination dependant)
	Maximum Analog Resolutions	1920x1200/1080p
	Maximum Digital Resolutions	1920x1200/1080p
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - Mini-DisplayPort (20 pin) Male
	Connector B	1 - HDMI (19 pin) Female
		1 - VGA (15 pin, High Density D-Sub) Female
		The UDMI next is a necessive next
Special Notes / Requirements	Note	The HDMI port is a passive port. The VGA port is an active port.
_	Humidity	
Requirements		The VGA port is an active port.
Requirements	Humidity	The VGA port is an active port. 10~85% RH
Requirements	Humidity Operating Temperature	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F)
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F)
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm]
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm]
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm]
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm]
Requirements Environmental Physical Characteristics Packaging	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width Weight of Product	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] 0.8 oz [22 g]
Requirements Environmental Physical Characteristics Packaging	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width Weight of Product Package Height	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] 0.8 oz [22 g] 0.6 in [15 mm]
Requirements Environmental Physical Characteristics Packaging	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width Weight of Product Package Height Package Length	The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] 0.8 oz [22 g] 0.6 in [15 mm] 8.7 in [22 cm]



Data Sheet

What's in the Box

Included in Package

1 - Mini DisplayPort™ to HDMI® / VGA Adapter

1 - Instruction manual

Product appearance and specifications are subject to change without notice.