# **HP Jetdirect 3000w NFC/Wireless Accessory**



Mobile printing accessory with easy setup, simple manageability and strong security.<sup>12</sup>



## Print from mobile devices - simply

- Deploy wireless direct printing and touch-to-print technology in a few simple steps 1,2,3
- Manage peer-to-peer printing at the device or HP Embedded Web Server, or fleet-wide using HP Web Jetadmin software.
- Users simply select a printer or MFP from their mobile devices to tackle tasks anywhere in the office.2
- Add the option to print from NFC-enabled mobile devices no network needed.23

## Go mobile – and stay protected

- Protect sensitive business information in transit and on the printer or MFP.
- Protect business information users can touch-to-print from mobile devices without accessing the network.3

# Multiple options, easy to control

- Easily print from a variety of smartphones and tablets generally no setup or apps required.2
- Clear wireless printing ports mobile devices automatically connect and disconnect from the printer or MFP.2

<sup>1</sup> HP 3000w NFC/Wireless Direct Accessory is compatible with select HP Laser Jet Enterprise printers and MFPs with HP FutureSmart Firmware, introduced fall 2015 and later. For a list of supported devices, see http://www.hp.com/go/mobileprinting.

<sup>2</sup> Feature is supported on select printers and may require purchase of an optional accessory. Mobile device needs to be connected directly to the WiFi network of a wireless direct-capable MFP or printer prior to printing.

Depending on mobile device, an app or driver may also be required. Learn more at http://www.hp.com/go/businessmobileprinting.

Requires a compatible NFC-printing-enabled mobile device. For a list of compatible NFC-printing-enabled mobile devices, see http://www.hp.com/go/nfcprinting.

<sup>4</sup> Universal device plug-in is offered with HP Web Jetadmin 10.3 SR4 and higher. HP Web Jetadmin is free and available for download at http://www.hp.com/go/webjetadmin.

# **HP Jetdirect 3000w NFC/Wireless Accessory**

## **Technical specifications**

What's in the box	
J8030A	HP Jetdirect 3000w NFC/Wireless Accessory; 2 mini USB cables; Stand-alone plastic cover; Velcro kit; Install guide
Compatibility	
Operating systems	See the printer data sheet for Compatible Network Operating Systems.
Printer supported	HP LaserJet M506, M527, M552, M553, M577, M604, M605, M606
Browsers supported	Internet Explorer 6.0 or higher; Mozilla 2.x or higher; Firefox 2.x or higher; Safari; Chrome
Connectivity	
Interfaces (standard)	802.11b/g Wireless Ethernet; NFC; Hi-Speed USB 2.0
Memory	
Standard	None (uses memory in printer)
Flash	None (uses storage in printer)
Environmental ranges	
Operating temperature	0 to 40°C
Recommended operating temperature	0 to 40℃
Storage temperature	-40 to 70ºC
Operating humidity	15 to 95% at 40℃
Recommended operating humidity	15 to 95% at 40℃
Storage humidity	15 to 95% at 65℃
Print Server Specifications	
Network types	Wireless (802.11 b/g)
Print server type	External, HIP2 (Hardware Integration Pocket)
Embedded Web Server	Yes
Install, configure, and manage with HP Web Jetadmin	Yes
Upgradeable firmware	Yes
Security management description	Management security: SNMPv3, SSL/TLS (HTTPS); Wireless network security: WPA2-Personal (WPA2-AES); Administrator password; (Same security protocols as attached Printer/MFP)
Dimensions (w x d x h)	
Product dimensions	82 x 56 x 20 mm
Packaged	178 x 138 x 60 mm
Weight	
Product weight	0.061 kg
Packaged	0.266 kg
Power consumption	
Maximum	2.5 watts (maximum)
Power requirements	Host USB powered accessory; Input voltage: 5 V, 500 mA
Power supply type	None (USB host bus driven)
Certification	
Safety	EU (Low Voltage Directive 2006/95/EC); EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011
Electromagnetic	EU (EMC Directive 2004/108/EC); EN 301 489-1 V1.9.2; EN 489-17 V2.1.1
Telecom compliance	Wireless telecommunications: EU (R&TTE Directive 1999/5/EC); EN 300 328; EN 62311
Environmental specifications	Complies with RoHS Directive 2011/65/EU; EN50581:2012
Warranty	
	One-year replacement warranty

