



## VS-211H2

2x1 4K HDR HDCP 2.2 HDMI Auto Switcher

| HDMI | HDCP Compliant | 4K/60 UHD (4:2:0)  
| 4K/60 UHD (4:4:4)



VS-211H2 is a high-performance automatic switcher for 4K HDR, HDCP 2.2, HDMI 2.0 video signals. Offering priority and last-connected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

### FEATURES

- Max. Data Rate - 17.82Gbps (5.94Gbps per data channel)
- Max. Resolution - 4K@60Hz (4:4:4)
- Kramer Equalization and re-Klocking Technology
- HDR Support
- HDTV Compatible
- HDMI 2.0 & HDCP 2.2 Compliant
- 3D Pass-Through



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	2 HDMI connectors
OUTPUTS:	1 HDMI connector
Max. Data Rate	17.82GBPS (5.94Gbps per graphic channel)
Max. Resolution	4K@60Hz (4:4:4)
Standards Compliance	HDR10, HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 2.0
CONTROLS:	Status/priority DIP-switches, contact closure remote control
REGULATORY CERTIFICATION:	EMC EN 55032;IEC 60950-1(ed.2);IEC 60950-1(ed.2)am1;IEC 60950-1(ed.2)am2
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
SHIPPING WEIGHT:	0.6kg (1.4lbs) approx
HUMIDITY:	10% to 90%, RHL non-condensing
POWER CONSUMPTION:	5V DC, 400mA
INCLUDED ACCESSORIES:	Power supply 5.2V DC/4A desktop
OPTIONS:	RK-3T 19" rack adapter

