

## PT-101H2

4K HDR HDMI Repeater

| HDMI | 4K/60 UHD (4:4:4) | 4K HDR



PT-101H2 is a high-performance 4K HDR repeater and extender for HDMI and HDCP 2.2 signals. For 4K@30Hz, it extends the range up to 20m (66ft) (15m to the input, 5m from the output)

## **FEATURES**

Max. Resolution - 4K@60Hz (4:4:4)

Range Extension - 4K@60Hz (4:4:4) up to 10m (33ft), (5m on the input to the PT-101H2 and 5m on the output); 4K@30Hz (4:4:4) up to 20m (66ft) (15m on the input to the PT-101H2 and 5m on the output)

Max. Data Rate - 17.82Gbps (5.94Gbps per data channel)

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

HDMI Output Power Follows Input HDR (High Dynamic Range) Support Transparent HDCP 2.2 Support



## TECHNICAL SPECIFICATIONS

INPUT: 1 HDMI on an HDMI connector

**OUTPUT:** 1 HDMI on an HDMI connector

MAX. DATA RATE: Supports up to 17.82Gbps (5.94Gbps per graphic channel

MAX. RESOLUTION: Up to 4K @60Hz 4:4:4

**COMPLIANCE WITH** HDR10 as specified in HDMI 2.0, HDCP 1.4, HDCP 2.2

HDMI STANDARD:

INDICATOR LED: ON

POWER SOURCE: 5V DC, 230mA

**OPERATING** TEMPERATURE: 0° to +40°C (32° to 104°F)

STORAGE  $-40^{\circ}$  to  $+70^{\circ}$ C ( $-40^{\circ}$  to  $158^{\circ}$ F)

TEMPERATURE:

**HUMIDITY**: 10% to 90%, RHL non-condensing

COOLING: Convection

ENCLOSURE TYPE: Aluminum

RACK MOUNT: With optional adapter

FURNITURE MOUNT: With included rubber feet

CE

VIBRATION: ISTA 1A in carton (International Safe Transit Association)

REGULATORY COMPLIANCE:

**ENVIRONMENTAL** Complies with appropriate requirements of RoHs and WEEE

REGULATORY COMPLIANCE:

INCLUDED

Power supply 5.2V DC 2A ACCESSORIES:

WARRANTY: 7 years parts and labor

**Product Dimension** 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

**Product Weight** 0.1kg (0.2lbs) approx

**Shipping Dimension** 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

Shipping Weight 0.5kg (1.1lbs) approx

