

HPE 453154-B21 Compatible SFP Module - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 1GE Gigabit Ethernet SFP - RJ-45 100m - HPE 6120XG, 6120G, Flex Fabric

Product ID: 453154B21ST



The 453154B21ST is a TAA compliant HPE 453154-B21 compatible copper transceiver module that has been designed, programmed and tested to work with HPE brand switches and routers. It delivers dependable 1 GbE connectivity over copper cable, for 1000BASE-T compliant networks, with a maximum distance of up to 100 m (328 ft).

Technical Specifications:

• Maximum Data Transfer Rate: 1000 Mbps

• Type: Copper

• Connection Type: RJ45 Connector

• Maximum Transfer Distance: 100 m (328 ft)

• MTBF: 805,386 hours

• Power Consumption: Less than 1.3 Watt

• Digital Diagnostics Monitoring (DDM): No

This SFP copper module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

Certifications, Reports and Compatibility



















Applications

- Replacing defective or damaged SFP modulesin HP switches and routers
- Expand your network to remote segments

Features

- 100% HPE 453154-B21 COMPATIBLE: Works with HPE switches like 6120XG, 6120G, Flex Fabric, BLc 7000, BladeSystem and others
- TECHNICAL SPECS: 1000BASE-T 1Gbps Copper RJ-45 Connector Distances up to 100m (328ft)
- TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in HPE routers and switches
- THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance
- WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules

Hardware		
	Warranty	Lifetime
	Compatible Brand	HPE
	Industry Standards	IEEE 802.3ab 1000BASE-T
Performance	Maximum Data Transfer Rate	1000 Mbps
	Max Transfer Distance	100 m (328 ft)

Copper

DDM No

Type

Compatible Networks 1000 Mbps (1 Gbps)

MTBF 805,386 hours



	Watts)	< 1.3 VV
Connector(s)		
	Local Unit Connectors	1 - RJ-45
Environmental		
	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	-40C to 85C (-40F to 185F)
	Humidity	5~95% RH
Physical Characteristics		
	Product Length	2.9 in [74.8 mm]
	Product Width	0.6 in [15.1 mm]
	Product Height	0.6 in [15.7 mm]
	Weight of Product	0.8 oz [24.0 g]
Packaging Information		
	Package Length	4.8 in [12.2 cm]
	Package Width	3.0 in [75.0 mm]
	Package Height	1.3 in [33.0 mm]
	Shipping (Package) Weight	2.0 oz [56.0 g]
What's in the Box		4. OFD :
	Included in Package	1 - SFP transceiver

< 1.3 W

Power Consumption (In

^{*}Product appearance and specifications are subject to change without notice.