

USB C to Serial Adapter Cable 16" (40cm) - USB Type C to RS232 (DB9) Converter Cable - USB-C Serial Cable for PLCs, Scanners, Printers - Male/Male - Windows/Mac/Linux

Product ID: ICUSB232C



This USB-C to serial adapter lets you connect your USB-C devices to your legacy serial equipment. It converts a USB-C port on your laptop or computer into a RS232 DB9 serial port, giving you a cost-saving way to connect to serial devices such as point-of-sale terminals, serial modems, industrial equipment, and a wide variety of other RS232 peripherals.

The RS232 adapter cable is compatible with Windows, macOS and Linux operating systems, which makes it easy to integrate into mixed environments.

The USB-C to serial adapter is USB powered, so you don't need an additional external power supply. It's a compact solution that's easy to bring along with your laptop, when you're on the go.

The ICUSB232C is backed by a StarTech.com 2-year warranty and free lifetime technical support.



## **Certifications, Reports and Compatibility**



## Applications

• IT administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port

- Connect bar code scanners, receipt printers and other point of sale devices
- Connect, monitor and control industrial/automotive sensors and other sensitive equipment
- Connect and program LED and digital signage boards

## Features

• USB-C TO SERIAL: Interface with Serial RS-232 (DB9) equipment using this black USB Type-C Serial adapter converter cable; Male DB9 connector features screw-lock nuts; Cable length of 16" [40 cm]

• TECH SPECS: 921.6 Kbps baud 512 byte FIFO Data bits of 5/6/7/8 and stop bits 1/1.5/2 Parity Modes of None, Xon/Xoff, RTS/CTS, DTR/DSR Flow control options Odd/Even/Mark/Space/None

• APPLICATIONS: Using your laptop's USB-C port, control serial equipment such as PLCs, scanners, sensors, oscilloscopes, medical, scales or receipt printers; Use in manufacturing, scientific, automation

• HOST COMPATIBILITY: Driverless setup for easy install; Tested on major operating systems, including Windows 7 and up, macOS 10.11 and up, Linux 2.6 and up; USB bus powered

• STARTECH.COM ADVANTAGE: IT professionals choice for over 30 years; This RS232 Serial Adapter is backed for 2-years by StarTech.com, including free 24/5 North America based multi-lingual tech support

| Hardware    |                    |                     |
|-------------|--------------------|---------------------|
|             | Warranty           | 2 Years             |
|             | Ports              | 1                   |
|             | Interface          | Serial              |
|             | Bus Type           | USB-C               |
|             | Port Style         | Cable Adapters      |
|             | Industry Standards | USB 1.1/2.0 RS232   |
|             | Chipset ID         | Prolific - PL2303RA |
| Performance |                    |                     |
|             | Serial Protocol    | RS-232              |
|             | Max Baud Rate      | 921.6 Kbps          |
|             |                    |                     |



|                                 | Data Bits                        | 5, 6, 7, 8                                    |
|---------------------------------|----------------------------------|---|
|                                 | FIFO                             | 512 Bytes                                     |
|                                 | Flow Control                     | None, Xon/Xoff, RTS/CTS, DTR/DSR              |
|                                 | Parity                           | Odd, Even, Mark, Space, or None Parity Modes  |
|                                 | Stop Bits                        | 1, 1.5, 2                                     |
|                                 | MTBF                             | 30,000 Hours                                  |
| Connector(s)                    |                                  |   |
|                                 | Connector Type(s)                | 1 - USB Type-C (24-pin) USB 2.0 (480Mbps)     |
|                                 |                                  | 1 - DB-9 (9 pin, D-Sub)                       |
| Software                        |                                  |   |
|                                 | OS Compatibility                 | Windows 7, 8.1, 10, 11                        |
|                                 |                                  | Windows Server 2008 R2, 2012 R2, 2016, 2019   |
|                                 |                                  | macOS 10.11 and 10.15, 11.0, 12.0             |
|                                 |                                  | Linux 2.6.x to 4.4.x <i>LTS Versions only</i> |
|                                 | Microsoft WHQL Certified         | Yes   |
| Special Notes /<br>Requirements |                                  |   |
|                                 | System and Cable<br>Requirements | One available USB-C port                      |
| Power                           | Power Source                     | USB-Powered                                   |
| Environmental                   |                                  |   |
|                                 | Operating Temperature            | 0C to 60C (32F to 140F)                       |
|                                 | Storage Temperature              | -20C to 80C (-4F to 176F)                     |
|                                 | Humidity                         | 0~65% RH                                      |
| Physical<br>Characteristics     |                                  |   |
|                                 |                                  |   |
|                                 | Color                            | Black   |
|                                 | Color<br>Product Length          | Black<br>16.9 in [43 cm]                      |



|                          | Product Width                | 1.2 in [30 mm]           |
|--------------------------|------------------------------|--------------------------|
|                          | Product Height               | 0.6 in [1.5 cm]          |
|                          | Weight of Product            | 1.3 oz [36 g]            |
| Packaging<br>Information |                              |                          |
|                          | Package Length               | 8.7 in [22 cm]           |
|                          | Package Width                | 7.9 in [20 cm]           |
|                          | Package Height               | 0.0 in [0.1 mm]          |
|                          | Shipping (Package)<br>Weight | 1.8 oz [52 g]            |
| What's in the Box        |                              |                          |
|                          | Included in Package          | 1 - serial adapter cable |
|                          |                              | 1 - quick-start guide    |

\*Product appearance and specifications are subject to change without notice.

