

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA

Telephone: 773.869.1234 www.tripplite.com

USB-C to DisplayPort Active Adapter Cable (M/M), 4K 60 Hz, 10 ft. (3.1 m)

MODEL NUMBER: U444-010-DP











Connects your existing DisplayPort monitor or projector to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, smartphone or PC. Saves you the clutter and expense of additional cables and adapters.

Description

The U444-010-DP USB 3.1 Gen 1 USB-C to DisplayPort 4K Adapter Cable (M/M) helps you transmit digital audio and 4K video from your tablet, laptop, Chromebook, MacBook, smartphone or PC to a DisplayPort-enabled monitor or projector. It's an ideal tool for giving video presentations in conference rooms and classrooms, editing multiple documents on a larger screen, or streaming video for digital signage in crystal-clear 4K.

With a source device that also supports USB DisplayPort Alternate Mode, you can extend 4K video from your primary display to another, duplicate the same video on both displays, or change the second display to your primary. By connecting to an existing DisplayPort display, you'll save the clutter of adding more cables and adapters.

The plug-and-play U444-010-DP requires no software, drivers or external power. Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time. Then, connect the DisplayPort plug to your display.

This 10-ft. (3.05 m) cable supports UHD video resolutions up to 3840 x 2160 (4K) at 60 Hz, 36-bit Deep Color (12 bits per channel) and per-lane transfer rates of 5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR). It also supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps. Foil and braid shielding protects against EMI/RFI line noise that can distort or destroy data.

Features

Connects a DisplayPort Display to Your USB-C or Thunderbolt 3 DeviceCompatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Modeldeal for giving video presentations, editing multiple documents, or streaming 4K video for digital signageSupports USB 3.1 Gen 1 data transfer rates up to 5 GbpsSupports DisplayPort 1.2 specificationsExtend 4K video from your primary display to another, duplicate the same video on both, or convert a secondary display to be your primary display

Crystal-Clear 4K Video and Digital AudioSupports UHD video resolutions up to 3840 x 2160 (4K) @ 60 HzSupports 36-bit Deep Color (12 bits per channel)Supports per-lane transfer rates of 5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR)

Reversible USB-C ConnectorFumble-free reversible USB-C plug connects in either direction for quick connection every time

Highlights

- Supports USB DisplayPort Alternate Mode for transmitting audio/video
- Supports UHD video resolutions up to 4K @ 60 Hz
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required
- Note: This cable is unidirectional. Will only work from a USB-C port to DisplayPort

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DisplayPort input

Package Includes

 U444-010-DP USB 3.1 Gen 1 USB-C to DisplayPort 4K Adapter Cable (M/M), 10-ft. (3.05 m)

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234



Premium ConstructionGold-plated connectors and contacts for maximum conductivity and minimum data lossFoil and braid shielding protects against EMI/RFI line noise that can distort or destroy dataIntegral strain relief helps cable and connectors move freely without stress or crackingDurable PVC jacket designed to last a long time

Ready for Instant UsePlug-and-play operation with no software, drivers or external power required10-ft. (3.05 m) length allows adaptable placement of source and display devicesBackward compatible with non-4K displays

Locking DP Connector Helps Prevent Accidental Disconnection and Expensive Downtime Having a cable come loose accidentally can mean costly and time-consuming signal loss. The locking DisplayPort connector helps you avoid such danger, protecting your audio/video transmission by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the cord always stays connected.

Specifications

OVERVIEW		
UPC Code	037332193858	
Product Type	Active Cable	
Technology	DisplayPort	
VIDEO		
Max Supported Video Resolution	DP: 3840 X 2160 (4K) @ 60HZ	
HDR Support	Yes	
INPUT		
Bus Powered	Yes	
Product Length (in.)	120	
Product Length (cm.)	304.8	
Product Length (ft.)	10	
Product Length (m.)	3.05	
BATTERY		
Battery Charging (5V/1.5A Port)	No	
POWER		
Power Consumption (Watts)	0.6	
PHYSICAL		
Material of Construction	PVC, ABS	
Color	Black	
Cable Jacket Color	Black	





66 x 17.78 x 1.27 0 x 7.00 x 0.50 4 bag o 113 F (0 to 45 C) o 158 F (-10 to 70 C) BTU/Hr s to 85% RH, non-condensing
06 x 17.78 x 1.27 0 x 7.00 x 0.50 4 2/bag 10 113 F (0 to 45 C) 10 158 F (-10 to 70 C) BTU/Hr 10 to 85% RH, non-condensing
06 x 17.78 x 1.27 0 x 7.00 x 0.50 4 2/bag 10 113 F (0 to 45 C) 10 158 F (-10 to 70 C) BTU/Hr 10 to 85% RH, non-condensing
0 x 7.00 x 0.50 4 by bag 10 113 F (0 to 45 C) 10 158 F (-10 to 70 C) BTU/Hr 15 to 85% RH, non-condensing
/bag to 113 F (0 to 45 C) to 158 F (-10 to 70 C) BTU/Hr to 85% RH, non-condensing
/bag to 113 F (0 to 45 C) to 158 F (-10 to 70 C) BTU/Hr to 85% RH, non-condensing
/bag 0 113 F (0 to 45 C) 10 158 F (-10 to 70 C) BTU/Hr 15 to 85% RH, non-condensing
o 113 F (0 to 45 C) o 158 F (-10 to 70 C) BTU/Hr o to 85% RH, non-condensing
o 113 F (0 to 45 C) o 158 F (-10 to 70 C) BTU/Hr o to 85% RH, non-condensing
o 113 F (0 to 45 C) o 158 F (-10 to 70 C) BTU/Hr o to 85% RH, non-condensing
o 158 F (-10 to 70 C) BTU/Hr 5 to 85% RH, non-condensing
o 158 F (-10 to 70 C) BTU/Hr 5 to 85% RH, non-condensing
BTU/Hr 5 to 85% RH, non-condensing
to 85% RH, non-condensing
to 000/ DLL non condensing
to 90% RH, non-condensing
3 C (MALE)
PLAYPORT (MALE)
t
3 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
ted to CE, FCC, RoHS, REACH
F d = -



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies