FX-89011

DATASHEET / BROCHURE





Nine-pin dot matrix printer offering faster printing, outstanding reliability and extremely low TCO.

The FX-890II is a high-volume, low TCO 80-column dot matrix printer designed for fast, reliable printing. A contemporary new design and smaller footprint make upgrading easy and add a range of new features for unprecedented flexibility.

Market-leading print speeds1

The FX-890II offers an improved USD (ultra speed draft) speed of 735 characters per second at 12 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

Outstanding reliability

Epson's dot matrix technology is already mature and very reliable, and these new printers improve the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

Smaller footprint

Epson's new range of dot matrix printers has a refreshed design with a smaller footprint - depth has been reduced to just 320mm - making it easy to place into a business environment.

KEY FEATURES

- Market-leading print speeds
 Complete high-volume print runs even faster
- Very low TCO
 Cheap, long-lasting consumables and low power use
- Even better reliability
 Improved by 25% to 25,000 power-on hours
- Smaller footprint
 Allows for easy placement within a business environment
- Energy Star compliant

 To ensure the best possible energy efficiency



PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins 9 pins Number of columns 80 columns

PRINT

Printing Speed HighSpeed-Draft: 10 cpi: 612 chars/s, Draft: 10 cpi: 463 chars/s, NLQ: 10 cpi: 115 chars/s Coda bar (NW-7), Code 128, Code 39, Industrial 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E Barcodes

Carbon Copies 6 plus one original

Character Tables PCAPTEC, PC437, PC720, PC850, PC858, ISO-8859-15, Roman 8, Italic

Character Sets 42

Printing Resolution 240 x 144 dpi

CONNECTIVITY

Interfaces USB - compatible with USB 2.0 specification, Bidirectional parallel, Ethernet interface (100

Base-TX / 10 Base-T)

PAPER / MEDIA HANDLING

Document Feed Single sheet front and rear, Continuous paper front and rear, Paper output rear

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes,

Cardboard

Paper Thickness Continuous 0.46 mm

Paper

Paper Thickness Label Base 0.46 mm

Sheet

Paper Thickness Multi Part 0.12 mm - 0.46 mm Paper Thickness Single Sheet 0.06 mm - 0.14 mm

GENERAL

54 W, 0.5 W (economy), 8 W (standby) **Energy Use**

Supply Voltage AC 198 V - 264 V

Energy Star Yes

Product dimensions 414 x 320 x 177 mm (Width x Depth x Height)

Product weight 7.2 kg

Operation 5° C - 35° C. Storage -30° C - 60° C Temperature

Mean Time Between Failures 25,000 Hours

Print Head Life 400 Million Strokes/Wire

Fonts Bitmap font EPSON Draft (10 CPI, 12 CPI, 15 CPI), Bitmap font EPSON OCR-B (10 CPI),

Bitmap font EPSON Roman (10 CPI, 12 CPI, 15 CPI, Proportional), Bitmap font EPSON Sans

www.epson.co.uk

www.epson.ie

Serif (10 CPI, 12 CPI, 15 CPI, Proportional)

Ribbon Yield 7 characters Black Draft

Operation 10% - 80%, Storage 30% - 60% Humidity

OTHER FEATURES

Emulations ESC/P. IBM PPDS

Input Data Buffer

LOGISTICS INFORMATION

SKU	C11CF37402
EAN code	8715946634494
Country of Origin	Indonesia

FX-890II

WHAT'S IN THE BOX

- Driver and utilities (CD)
- User guide
- AC cable
- Ribbon

SUPPLIES

• Epson SIDM Black Ribbon Cartridge for FX-890, FX-890A (C13S015329) (C13S015329)

OPTIONAL ACCESSORIES

- SIDM FX-890II, LQ-590II Pull Tractor Unit C12C933761
- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series C12C811141

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742

Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

1. Speeds compared with published specifications for directly competing products, May 2017.

