

QNA-T310G1T

Network Adapters	Thunderbolt to 10GbE
PHY IC	AQC107S
I/O	1 x Thunderbolt 3, 1 x 10GbE/NBASE-T connector
Transmission rates	10Gbps/5Gbps/2.5Gbps/1Gbps/100Mbps
Package content	QNA-T310G1T, 0.5M Thunderbolt 3 cable and manual
Port and cable	RJ-45; Cat 6a cable recommended
Note	 Windows® devices: The driver for the Marvell AQtion AQC107 is required to use the QNA-T310G1T. <u>Click here to download drivers</u> Mac devices: Requires macOS 10.13.3 (or later). Linux: Supports Linux core 3.10, 3.12, 3.2, 4.2, and 4.4. The driver for the Marvell AQtion AQC107 is required to use the QNA-T310G1T. <u>Click here to download drivers</u> QNAP Thunderbolt[™] 3 NAS: Requires QTS 4.3.6 (or later).

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. * Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.