

HCH-3010RU-CHG

Charger Specifications:

Dimensions:

Length: 108.0 mm
 Width: 152.0 mm
 Height: 127.0 mm
 weight: 400.0 g

Temperature:

Operating (low): 0.0°C 32.0°F
 Operating (high): 40.0°C 104.0°F

Storage (low): -10.0°C 14.0°F
 Storage (high): 50.0°C 122.0°F

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



GTS Batteries

HMC3X00-Li(S) and HMC3X00-Li(H)

Battery Features:

- Compliant with Symbol charger suite.
- 2 year warranty to maintain 80% capacity, materials and workmanship.
- Capacity of 3100 mAh.
- Improved cycle life and operational runtime between recharging.
- Improved latch design.

Maximize the performance of the Symbol® MC3000/MC3100 Series Mobile Computers



Dual-chemistry: Support Li-Ion & Li-Polymer.

Tri-color charging indications: Charging LED indicates charging status.

Hassle-free mounting: Utilizes same mounting brackets as OEM chargers for easy wall mounting.

Designed for users who do not need a second battery: Holds and charge one device.

Made of highly rugged aerospace grade aluminum housing.

Includes power supplies and cable.

Can easily be customized to meet your customer needs.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
 550 Cochituate Road Framingham, MA 01701
 US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

