

SPECIFICATIONS

MODEL NAME

SPEAKER FREQUENCY

2014- 2014-

RESPONSE
CONNECTOR
20Hz~20KHz
2.0 USB

CABLE 2.2m with gold-plated connector

PRODUCT DIMENSION (MM)

DRIVER UNIT

SPEAKER SENSITIVITY (SPL)

SPEAKER IMPENDANCE

PICK-UP PATTERN

MICROPHONE SENSITIVITY

170 x 80 x 200mm
40mm Neodymium
109 dB ± 3 dB
32 ohm ± 15%
Unidirectional

MICROPHONE SENSITIVITY
A36 dB ± 3 dB
MICROPHONE IMPEDANCE
2.2k ohm

MICROPHONE FREQUENCY 100 Hz~10 kHZ

OPERATING SYSTEM Windows 10 / 8.1 / 8 / 7 **WEIGHT (PRODUCT / PACKAGE)** 300g / 700g



FEATURES

- 2 x 40mm Neodymium drivers with virtual 7.1 surround sound and vibration system
- RGB Mystic Light with millions of colors and various effects
- Sturdy Metal Construction and foldable headband design
- Detachable microphone
- Inline controller for volume, muting mic,
 7.1 sound and vibration toggle
- Carry pouch included in retail box