









SPECIFICATION

Model Name	GeForce [®] GTX 1660 SUPER™ GAMING X
Graphics Processing Unit	NVIDIA [®] GeForce [®] GTX 1660 SUPER™
Interface	PCI Express x16 3.0
Cores	1408 Units
Core Clocks	Boost: 1830 MHz
Memory Speed	14 Gbps
Memory	6GB GDDR6
Memory Bus	192-bit
Output	DisplayPort x 3 (v1.4) / HDMI 2.0b x 1
HDCP Support	2.2
Power consumption	125 W
Power connectors	8-pin x 1
Recommended PSU	450 W
Card Dimension(mm)	247 x 127 x 46 mm
Weight (Card / Package)	862g / 1460 g
Afterburner OC	Υ
DirectX Version Support	12 API
OpenGL Version Support	4.5
Maximum Displays	4
VR Ready	Y
G-SYNC [®] technology	Y
Adaptive Vertical Sync	Υ
Digital Maximum Resolution	7680x4320

CONNECTIONS



DisplayPort	
HDMI	

1. 2

FEATURE



TORX FAN 3.0

Award-winning fan design combining two different fin designs for cool & quiet gaming.

Mastery of Aerodynamics

Using groundbreaking aerodynamic techniques, the heatsink is optimized for efficient heat dissipation.

ZERO FROZR

Eliminates fan noise by stopping the fans in low-load situations so you can focus on your game.


CUSTOM PCB

An optimized PCB design with enhanced power delivery provides a solid base for high performance gaming.

SOLID BACKPLATE

Increases toughness of the card to prevent bending while complementing the design.

DRAGON CENTER



OC PERFORMANCE



MSI OC graphics cards are equipped with higher clock speeds out of the box for increased performance.

MSI Afterburner



The ultimate overclocking software with advanced control options and real-time hardware monitor.

TRUE GAMING © 2018 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved. © 2016 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.





