

PD43 & PD43C SERIES

Light Industrial Thermal Printer

The PD43 and smaller PD43c series of light industrial thermal printers incorporate the latest printing innovations into a compact and affordable solution designed to deliver uncompromising print performance in the smallest possible footprint.

Suited for the distribution center and warehouse, as well as airline passenger service, the PD43 upholds the long tradition of the PD series. An all-metal chassis, strong cast aluminum print mechanism, and tool-free printhead and roller replacement help minimize downtime and maintenance needs. With a variety of door options, the PD43 can support a wide range of media, including link-in and link-out ribbons with half-inch or one-inch core sizes - enabling maximum time between media resupply. Fast-time-to-label and print speeds of up to 200 mm/s (8 ips) ensure that the PD43 can scale with the changing needs of dynamic operations.

The PD43 takes industrial printing to a new level of simplicity, with a color graphic display that makes it easier to set up, configure and fine-tune settings without the need for a host computer. In fact, with Smart Printing capabilities, the PD43 can run apps right inside the printer - eliminating the need for a connected PC entirely.

Considering the switch to PD43 series from another printer brand? With comprehensive command language support - including ZSim2, our fast, friendly, and complete ZPL II® emulation - updating to the PD series has never been easier.



Combining the latest printing innovations into a compact, rugged package, the PD43 series is ideal for use in tight spaces, on shallow countertops, or in pull-out cabinets.

Add a service plan from Honeywell Repair Service and ensure business continuity, workflow performance and protection of your technology investments - now available in more than 70 countries with global pricing and global standards of quality.

FEATURES AND BENEFITS



Small footprint for installation into compact tabletops and pull-out cabinets.



Rugged metal chassis and print mechanism provides investment protection.



Intuitive 10-language color display or icon interface simplifies setup and maintenance.



Comprehensive printer command language support, including ZSim2, makes upgrading easy.



Run apps right inside the printer control peripherals and eliminate the need for a connected PC, using C# for Printers or Fingerprint.

PD43 & PD43C SERIES Technical Specifications

PHYSICAL CHARACTERISTICS

PD43 with Standard Door:

Length: 470 mm (18.5 in)
Width: 211 mm (8.3 in)
Height: 249 mm (9.8 in)
Weight: 8.4 kg (18.5 lbs)

PD43 with Flat Top Door:

Length: 470 mm (18.5 in)
Width: 211 mm (8.3 in)
Height: 209 mm (8.2 in)
Weight: 8.3 kg (18.3 lbs)

PD43c:

Length: 236 mm (9.3 in)
Width: 211 mm (8.3 in)
Height: 205 mm (8.1 in)
Weight: 5.1 kg (11.2 lbs)

PD43c with Optional External Media Holder:

Length: 432 mm (17.0 in)
Width: 211 mm (8.3 in)
Height: 217 mm (8.5 in)
Weight: 6.0 kg (13.2 lbs)

MEDIA COMPATIBILITY

Max. Media Diameter (OD):

PD43 with Standard Door: 213 mm (8.375 in)
PD43 with Flat Top Door: 152 mm (6.0 in)
PD43c with External Media Holder: 203 mm (8.0 in)

Media Core Sizes (ID):

1, 1.5, 3 in
Media Width: 19mm (0.75 in) to 118 mm (4.65 in)
Label Length: 6.4 mm (0.25 in) to 172.7 cm (68.0 in)

RIBBON COMPATIBILITY

Ribbon Support:

Coated Side In, Coated Side Out
Max. Ribbon Diameter: 68mm (2.68 in)
Ribbon Core Sizes: 0.5, 1 in
Ribbon Width: 25.4 mm (1 in) to 110.0 mm (4.3 in)
Max. Ribbon Length: 300 m (984 ft)

PRINTING CHARACTERISTICS

Print Resolution : 8.0 dpmm (203 dpi), 11.8 dpmm (300 dpi)
Max. Print Speed: 203 mm/s (8.0 ips) @ 8.0 dpmm (203 dpi), 152 mm/s (6.0 ips) @ 11.8 dpmm (300 dpi)
Max. Print Width: 104 mm (4.1 in)

For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Baires Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com

COMMUNICATIONS

Standard Interfaces:

USB Device, USB Host¹
Optional – Via Adapter Cables: Internal Ethernet (NIC), Parallel Port, Serial Port
Optional – Factory/Service Installable: Bluetooth® and Wireless 802.11 b/g/n, HF/UHF RFID, Internal Ethernet (NIC)
Protocols – Wireless: WEP Dynamic; WEP Static (64/128 bits); WPA; WPA2; EAP (FAST, PEAP, TLS, TTLS); LEAP
Protocols – Serial Flow Control: XON/XOFF, RTS/CTS (DTR/DSR)
Certifications: Cisco® CCXv4, Wi-Fi

USER INTERFACE

Display:

Color Graphic Display or Icon Display
Languages – Standard: English, French, German, Italian, Portuguese, Russian, Spanish
Languages – Optional: Simplified Chinese, Traditional Chinese, Korean

GRAPHICS & BAR CODES

Native Graphic Formats: BMP, GIF, PCX, PNG
Barcode Symbolologies: All Major 1D, 2D, and Composite Symbolologies

SOFTWARE

Printer Command Languages: Direct Protocol, IPL, DPL, ESIm (EPL), ZSim2 (ZPL II®), XML-Enabled for SAP All and Oracle® WMS
Smart Printing Languages: C# for Printers, Fingerprint

Developer Tools : Smart Printing Developer Resource Kit, Honeywell Fingerprint Application Builder (IFAB)

Applications & Drivers : InterDriver Windows® Printer Driver, CUPS Driver for Linux, Device Types for SAP, BarTender Ultralite

Device Management: PrintSet, SmartSystems™, Wavelink Avalanche™

Character Sets : English & Extended Latin, Arabic, Baltic & Baltic Rim, Cyrillic, Greek, Hebrew, Thai, Turkish, Vietnamese and more with Monotype Universal Font Scaling Technology (UFST®) and WorldType Layout Engine (WTLE)

Resident Fonts: Andale Mono, Andale Mono Bold, Century Schoolbook, CG Times, CG Times Bold, CG Triumvirate Condensed Bold, Letter Gothic, OCR-A, OCR-B, Univers, Univers Bold, Univers Condensed Bold, Univers Extra

Additional Fonts: Support for TrueType and TrueType-based OpenType fonts, user downloadable fonts

ENVIRONMENTAL

Operating Temperature: +5° to +40°C (+40° to +104°F) @ 10–80% RH Non-Condensing

Storage Temperature: -40° to +60°C (-40° to +140° F) @ 85% RH

ELECTRICAL

Input: 100–240V AC @ 50–60 Hz, 1.5 A, Energy Star Compliant

Output: 24V DC, 2.5 A

MEMORY

Standard: 128 MB Flash, 128 MB RAM (DDR2)

Optional: Up to 32 GB (via user USB thumbdrive)

OPTIONAL ACCESSORIES & UPGRADES

User Installable: 300 dpi, Cutter Unit with LTS, Label Dispenser with LTS, Front Label Tray, Linerless

Factory / Service Installable: HF RFID (13.56 MHz, ISO 15693); UHF RFID (EPC Class1 Gen2, ISO 18000-6C)

APPROVALS

Regulatory: UL, cUL, cULus, CE, FCC Class A, D Mark CCC, KCC, RCM

Safety: North America: UL & cUL Listed, UL60950-1; Europe: D Mark, EN 60950-1; CE; Mexico: NYCE Certified, NOM 19; Other Countries: IEC 60950-1

EMC: USA: FCC Title 47, Part 15, Subpart A, Class A; Europe: EMC Directive (EN55022 Class A + EN55024); CISPR22

WARRANTY

One-year standard warranty

¹ PD43 supports two USB Host connectors.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance. For a complete listing of all supported barcode symbolologies, please visit www.honeywellaidc.com/symbolologies.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.

Cisco is a trademark or registered trademark in the US and/or other countries of Cisco Systems, Inc.

Oracle is a trademark or registered trademark in the US and/or other countries of Oracle Corporation.

Windows is a trademark or registered trademark in the US and/or other countries of Microsoft Corporation.

SmartSystems is a trademark or registered trademark in the US and/or other countries of Honeywell International Inc.

Wavelength Avalanche is a trademark or registered trademark in the US and/or other countries of Wavelength Corporation.

UFST is a trademark or registered trademark in the US and/or other countries of Monotype Imaging, Inc.

ZPL II is a trademark of ZIH Corp., registered in many jurisdictions worldwide.