

Part No. 43278

## USB 3.1 TYPE C MULTI-PORT CONVERTER

CONNECT YOUR PERIPHERALS VIA A SINGLE USB TYPE C CABLE



### DESCRIPTION

- Adds 3 USB 3.1 Gen 1 / USB 3.0 Type A ports, an HDMI and VGA port as well as a Gigabit Ethernet port to a laptop
- Supports 4K UHD 3840x2160@30Hz for HDMI displays and Full HD 1920x1080@60Hz for VGA displays
- Features DisplayPort Alternate Mode
- USB Power Delivery 3.0 capable up to 100W
- 2 year warranty

The Lindy USB 3.1 Type C Multi-Port Converter is a compact and multifunctional solution for connecting Laptops to a range of interfaces including displays, all over a single Type C cable. Featuring all the interfaces needed for a modern workstation, this Multi-Port Converter uses a single USB 3.1 Type C cable to simultaneously connect a laptop to a display and provide power, Gigabit Ethernet and USB 3.1 Gen 1 / USB 3.0 SuperSpeed ports. It also features a card reader for SD and microSD cards.

The converter enables the connection of a display to a laptop via HDMI at resolutions of 3840x2160@30Hz or via VGA at 1920x1080@60Hz using DisplayPort Alternate Mode through the USB Type C port. If a VGA and HDMI display are connected simultaneously, this converter works as a splitter with maximum resolution of 1920x1080@60Hz for each display with the same video content.

With support for USB Power Delivery up to 100W it is also able to provide power to a laptop using the Type C port. The three integrated USB 3.1 Gen 1 / USB 3.0 Type A ports provide up to 5Gbps of data transfer. Perfect for connecting Type A peripherals such as a hard drive, printer or webcam.

### RELATED PRODUCTS

0

# USB 3.1 TYPE C MULTI-PORT CONVERTER

## SPECIFICATIONS

---

Interface	USB Type C to 1x VGA / 1x HDMI / 1x RJ45 / 3x USB 3.0 Type A / 1x microSD / 1x SD
Interface Standard	USB 3.1 Gen 1 / USB 3.0, VGA, HDMI, Gigabit LAN
Supported Bandwidth	5 Gbps, 10/100/1000Mbps
Maximum Input Resolution	3840x2160@30Hz
Maximum Output Resolution	3840x2160@30Hz (HDMI), 1920x1080@60Hz (VGA) simultaneous connection with the same video content: 1920x1080@60Hz each (VGA / HDMI)
Chipset	RTL8153B, EP9632G, GL3510
Compatibility	USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
Power Delivery	PD 3.0 up to 100W (20V 5A)
HDCP Support	HDCP2.2
Supported Audio	-
Seperate Audio Ports	-
Special Features	DisplayPort Alternate Mode

## CONNECTORS

---

Input	1 x USB Type C (Male)
Output	1x USB Type C (Female), 1x VGA (Female), 1x HDMI (Female), 1x RJ45 (Female), 3x USB Type A (Female), 1x SD slot, 1x microSD slot
Power	-

## PHYSICAL PROPERTIES

---

Dimensions (approx.) WxDxH	180x17x49mm (7.09x0.67x1.93in)
Housing Material	Aluminium
Net Weight	0.09kg (0.2lb)
Operating Temperature	0° - 45°C (32°F - 113°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	20 – 80% RH (non-condensing)
Power Requirements	Bus-powered
Colour	Grey

## MISCELLANEOUS

---

Packaging Type	Polybag
Packaging Dimension	174x194mm (6.85x7.64in)
Gross Weight	0.1kg (0.22lb)
Warranty (Years)	2
Certificated	CE, FCC, REACH & RoHS, CP65

## PURCHASING INFORMATION

---

No.	43278
EAN	4002888432788

## PACKAGING CONTENTS

---

USB 3.1 Type C Multi-Port Converter  
Lindy Manual