

USB Video Capture Adapter Cable - S-Video/Composite to USB 2.0 SD Video Capture Device Cable - TWAIN Support - Analog to Digital Converter for Media Storage - Windows Only

Product ID: SVID2USB232



This USB video capture adapter offers an easy to use analog video capture solution, enabling you to convert video (and accompanying audio) from a composite or S Video source to your Windows-based computer.

Broad Capabilities

An easy-to-use device for recording analog video to your PC from external sources, such as a VCR or camcorder, the S Video and composite to USB converter offers the perfect solution for Betamax or VHS video capture, with real-time MPEG-1, MPEG-2, and MPEG-4 encoding.

This analog to digital video adapter is ideal for converting VHS or home movies to digital format, as well as importing videos onto your Windows computer for editing. It also features a snapshot function that enables users to capture still images from their analog video.





Conveniently Compatible

This analog video capture cable delivers seamless analog video capture for your Windows devices. As well, the S Video / composite to USB adapter has TWAIN support, to ensure compatibility with a wide range of systems and software.

Small Form Factor Design

This analog to digital converter cable connects to your PC through USB 2.0 and is compact enough to fit in the palm of your hand, providing a conveniently portable video capture solution that's more than suitable for use with laptops and desktop computers alike.

SVID2USB232 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Note: This converter is for use with Windows-based devices only and is not compatible with macOS.





Certifications, Reports and Compatibility











Applications

- Digitally record and view content from your reliable legacy equipment
- Convert your VHS home movies to digital format
- Connect your VCR or other analog source to your PC and capture audio/video in MPEG 1/2/4 format

Features

- SD VIDEO CAPTURE: USB video capture adapter converts composite/S-Video & RCA 2ch audio into digital media; supports 30fps @720x480i (NTSC)/25fps @720x576 (PAL/SECAM) & MPEG-1/MPEG-2/MPEG-4 encoding
- SOFTWARE COMPATIBILITY: USB 2.0 video capture cable drivers are TWAIN compatible for use w/ third-party software; incl. software provides an out of the box solution for Windows (7-10) computers
- CAPTURE & SHARE: Using third-party software (OBS, etc.) you can capture standard def 480i video and stream on services like YouTube (or other social media platforms) or in training & resource centers
- PORTABLE DESIGN: USB bus-powered USB video capture device is compact & lightweight, so you can easily take it from your media room or classroom while in the office, working from home or on the go
- ANALOG TO DIGITAL VIDEO CONVERTER: Use the intuitive Windows software (included) to easily capture video from your VCR/BETA, camcorder or home videos VHS to Digital/DVD or PC storage



Data Sheet

	Warranty	2 Years
Hardware	Audio	Yes
	AV Input	Audio RCA
		Composite
		S-Video
	AV Output	USB
	Chipset ID	EM28281
	Industry Standards	NTSC, PAL, SECAM
		Video Encoding: MPEG 1, MPEG 2, and MPEG 4
		DirectShow Compatible
Performance	Maximum Analog Resolutions	720x480(NTSC) / 720x576(PAL)
	Maximum Data Transfer Rate	480Mbps
Connector(s)	Connector A	1 - USB Type-A (4 pin) USB 2.0 Male Output
	Connector B	1 - Composite Video (1 x RCA) Female Input
		1 - Stereo Audio (2 x RCA) Female Input
		1 - S-Video (4 pin, Mini-DIN) Female Input
Special Notes / Requirements	Note	This converter is for use with Windows-based devices only and is not compatible with macOS
_	Note Humidity	
Requirements		and is not compatible with macOS
Requirements	Humidity	and is not compatible with macOS 5~85% RH Non-condensing
Requirements	Humidity Operating Temperature	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F)
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F)
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Color	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Color Material	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black Plastic
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Color Material Product Height	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black Plastic 34.000
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Color Material Product Height Product Length	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black Plastic 34.000 130.000
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Color Material Product Height Product Length Product Width	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black Plastic 34.000 130.000 186.000
Requirements Environmental Physical Characteristics	Humidity Operating Temperature Storage Temperature Color Material Product Height Product Length Product Width Weight of Product	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black Plastic 34.000 130.000 186.000 181.000
Environmental Physical Characteristics Packaging	Humidity Operating Temperature Storage Temperature Color Material Product Height Product Length Product Width Weight of Product Package Height	and is not compatible with macOS 5~85% RH Non-condensing 0°C to 50°C (32°F to 122°F) -20°C to 60°C (-4°F to 140°F) Black Plastic 34.000 130.000 186.000 181.000 38.000



Data Sheet

What's in the Box	Included in Package	1 - USB 2.0 Capture Device
		1 - User Guide
		1 - Software CD
		1 - Driver CD

Product appearance and specifications are subject to change without notice.