

AXIS S3008 Recorder

Compact recorder with integrated switch for UHD surveillance

AXIS S3008 Recorder is a compact recorder with an integrated PoE switch for up to 8 cameras. It provides reliable recording thanks to the surveillance-grade hard drive. This high-performance recorder offers gigabit uplink for video recordings in ultra-high definition. Including a 5-year warranty, it is supported only by the AXIS Companion video management software and mobile app.

- > [Compact recorder with integrated PoE switch](#)
- > [Easy to install and operate](#)
- > [Surveillance-grade hard drive](#)
- > [USB port for exporting video](#)
- > [5-year warranty](#)



AXIS S3008 Recorder

Models	AXIS S3008 Recorder 2 TB AXIS S3008 Recorder 4 TB	Only PoE-class reservation is currently supported. Allocation of Max-power via LLDP under development
Storage	2 TB: 2 TB, surveillance class HDD 4 TB: 4 TB, surveillance class HDD	Casing Aluminum and plastic casing Color: Black
Video		Operating conditions 0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Recording	Qualified for recording up to 8 video sources with a total recording rate up to 160 Mbit per second	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH
Video compression	H.264 (MPEG-4 Part 10/AVC), H.265 (MPEG-H Part 2/HEVC) Depending on camera support	Connectors Rear side: 8x RJ45 10BASE-T/100BASE-TX PoE 1x RJ45 10BASE-T/100BASE-TX/1000BASE-T DC input Side: 1x USB 3.0
Resolution	Supports all camera resolutions	Approvals EMC: CISPR 24, CISPR 35, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCC1 Class A Safety: IEC/EN 62368-1, UL 62368-1 Environment: IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78, IEC/EN 60529 IP3X
Frame rate	Supports all camera frame rates	Sustainability PVC free
Audio streaming	One-way audio recording depending on camera support	Dimensions 180 x 180 x 53 mm (7 1/16 x 7 1/16 x 2 1/16 in)
Audio encoding	AAC Depending on camera support	Weight 2 TB: 1310 g (2.89 lb) 4 TB: 1350 g (2.98 lb)
Network		Included accessories AXIS Mains adapter 48V DC 90W (01508-001), installation guide
Network function	NTP server	Optional accessories AXIS TS3001 Recorder Mount
Security	Hard drive encryption (AES-XTS-Plain64 256bit), password protection, digest authentication, user access log, centralized certificate management, signed firmware, secure boot, IEEE 802.1x (EAP-TLS) network access control, Axis Edge Vault with Axis device ID	Video management software AXIS Companion version 4 available on axis.com/vms
Supported protocols	IPv4/v6, HTTP, SSL/TLS, QoS, SFTP, SMTP, Bonjour, UPnP™, DNS, NTP, TCP, UDP, IGMP, ICMP, DHCPv4/v6, ARP, SSH	Warranty Recorder: 5-year warranty, see axis.com/warranty Hard drive: 3-year limited hardware warranty
System integration		Environmental responsibility: axis.com/environmental-responsibility
Application Programming Interface	AXIS Video Hosting System (AVHS) with One-Click Connection	
Events & alarms		
Event triggers	Hard drive error, hard drive temperature warning, CPU temperature warning, fan error, PoE budget exceeded	
General		
Supported devices	Axis network cameras and encoders with firmware 8.40 or later AXIS Companion mini cameras are not supported	
Input	Power supply: 50–60 Hz, 100–240 V AC, max 90 W Recorder: 1.88 A, 48 V DC, max 90 W	
Output	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 0, Class 1, Class 2, and Class 3 65 W total PoE power budget	