

i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W

i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W



PRODUCT DESCRIPTION

Professional USB-C docking station with support for up to four external monitors. The docking station is equipped with hybrid image processing: it is built on DisplayLink and USB-C video transmission technologies, allowing it to process images on four display devices at the same time.

The station is compatible with any laptop equipped with a USB-C port (with video transmission support) or Thunderbolt 3. 6x USB ports, reliable and quick connection to your company network thanks to an integrated LAN port and support for installation on the back of a monitor make the docking station an ideal partner for professionals. And of course, the station is capable of charging your laptop or tablet with up to 85 W.

- Connect up to 4 external monitors
- Power delivery: up to 85 W
- Provides 2 DisplayPorts and 2 HDMI ports
- 5x USB 3.0 and 1x USB-C ports will allow you to easily connect your USB devices and peripherals.
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- 2x jack for audio and microphone
- Kensington lock protects against theft, particularly in shared offices or public spaces
- On/off switch for maximum energy savings
- The station features VESA support, allowing smart vertical installation on the back of a VESA compatible monitor
- Supports Windows 10, macOS*, Android, ChromeOS and Linux

PRODUCT FEATURES

^{*} Note: macOS does not support Multi Stream Transport (MST) technology, meaning that when connected to a device running macOS, two of the four connected monitors will display the same image.



- 1x USB-C port for connecting to a device
- Docking station technology: USB-C (MST) + DisplayLink 3900
- Power Delivery: 85W
- Video ports: 2x DisplayPort 2x HDMI
- Resolution:
- DisplayLink ports 2x HDMI
 - 1 monitor: up to 2560x1440/50Hz
 - 2 monitors: up to 2048x1152/60Hz
- USB-C DP Alt mode ports 2x DP DP 1.2 HBR2:
 - 1 monitor up to 4K/30Hz
 - 2 monitors up to 2x 1080p/60Hz
- DP 1.4 HBR3:
 - 1 monitor up to 4K/60Hz
 - \circ 2 monitors up to 2x 1440p/60Hz
- DP 1.4 HBR3 DSC:
 - 1 monitor up to 4K/60Hz
 - 2 monitors up to 2x 4K/60Hz
- (Four monitor combination): Up to 2x 2048x1152/60 Hz and 2x 4K/60 Hz
- 1x USB-C Gen. 1 port (data only)
- 4x USB 3.0 port
- 1x USB 3.0 port with Fast Charge support (BC 1.2)
- 1x Ethernet GLAN RJ-45 port (Realtek RTL8153)
- 1x 3.5mm Audio port
- 1x 3.5mm Mic port
- 1x port for power supply (DC 20 V/6.75 A)
- ON/OFF switch for the docking station
- LED indication
- Kensington lock support
- VESA mount support
- Product dimensions: 197 x 85 x 34 mm
- Product weight: 290 g

Hardware requirements:

• Device with a free USB-C or Thunderbolt 3 port

Requirements for Power Delivery feature:

Device with a free USB-C or Thunderbolt 3 port with support for Power Delivery technology

Requirements for video output:

 Device with a free with a Thunderbolt 3 port or with a USB-C port with support for DisplayPort Alternate Mode technology

Operating system:

Windows 10, macOS*, Android, Chrome OS and Linux with the latest updates

SPECIFICATION

Part Number	Product Description & EAN

^{*} macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station via DisplayPorts on macOS will result in both monitors showing the same image.



C31QUATTRODOCKPD	i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W EAN: 8595611703393	
C31QUATTRODOCKPDUK	i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W EAN: 8595611703409	
Hardware		
Bus type	USB-C, Thunderbolt-3	
Ports/Connectors		
System Requirements		
Operating system	Windows 10 macOS X Android Linux Chrome OS R51 or laterWindows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.	
Other features		
Colour	black	
Housing Material	plastic	
Product Dimensions	197 x 85 x 34 mm	
Product Weight	290 g	
Package Weight		
Packaging Dimensions (LxWxH)		
Support		
Warranty period	2 years	
Technical support	lifetime	
Package contents		
Product		
USB-C cable (100 cm)		
Charging adapter (output: 20.0/4.75 A, 160 cm DC cable)		
Instruction manual		

For further information regarding setup or for answers to FAQ's, please visit our website $\underline{i\text{-tec.cz}}$. Specifications are subject to change without notice.

Updated 18.8.2020