



65" Android Based Interactive Flat Panel Displays

Key Features



Palm Erase

Automatic palm erasing function allows teachers and students to simplify the white board experience with smooth writing and erasing.



Wireless Presentation

Teachers, students or any user can share their screen efficiently and conveniently in the classroom or meeting room via EShare application. This application can connect any operating system and show up to 4 different screen at the same time.



Crestron Connected

Crestron Connected certification complements VESTELs presence with inside the corporate, retail, government, better training and hospitality markets, all of which use expert AV controls. As those sectors hold to evolve with growing necessities for simple-to-use merchandise, seamless integration, dependable answers and community connectivity.



Ease of use with Android

Android gives teachers one touch access for lessons and collaboration tools including whiteboard, web browser, apps library, and native wireless screen sharing.



Different Sizes for various classrooms

Available in a variety of large screen sizes, the IFD range gives customers the options to choose exactly what they need for their room size.



DISPLAY

Screen Size 65"

Direct-Type LED Panel Technology Backlight Type 350 cd/m²

UHD: 3840 x 2160 - HDR10 Native Resolution

1200.1 Contrast Ratio (typical) Dynamic Constrast Ratio 35000:1 30.000 hrs Panel Life Time (Min.) Life Time (typical) 8 ms

Active Area (H x V) 1428 x 804 mm Pixel Pitch (H x V) 0.372 x 0.372 mm

PPI (pixel per inch)

178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 Viewing Angle

Color Value 1.07 B (10-bit) Screen Treatment 2H Haze Level 8% 60 Hz Refresh Rate Front Type Touch Bezel Orientation Horizontal 16/7 Panel Operation Hours Area of Usage Indoor

BUILT-IN SYSTEM

Mainboard Model MB135VS

REAR I/OS

RGB Input VGA(DE-15F) RGB Output N/A

Video Input

3xHDMI2.0, 2xUSB2.0, USB2.0(Internal), 1xMicroSD

HDMI2.0 Video Output Audio Input Line In L/R

Audio Output Headphone, Optic SPDIF

RS232(DE-9F), 2*Ethernet(RJ45), Service(RJ12) External Control

External Sensor RJ12

TOUCH INTERACTIVITY

Type of Touch Technology Infrared (IR) Tech. - 10 Points

Any touch with finger, gloved hand or pointer Sensitivity

up to 450 fps

Connectivity HID. TUIO. Flash

Windows[®]7,Windows[®]8, Windows[®]10, Vista, XP, Mac Compatibility

[®] OS, Linux, Android Orientation Landscape support Calibration No need 90% < Accuracy

Reporting Rate Glass Type Anti Glared (AG), Tempered

Frame Rate up to 450 fps Communication USB 2.0 Power Supply Mode USB DC 5V +/- 5% Supply Voltage Average Current < 400 mA Response Time < 10 ms

Touch Accuracy +/- 2 mm (over 90% area)

Touch Durability Unlimited HID Compatibility Yes USB Object Sizes for Touch 5 mm

MECHANICAL

Product Dimensions (WxDxH) 1507 x 118 x 882 mm Package Dimensions (WxDxH) 1756 x 265 x 1100 mm

Product Weight 38.6 kg Package Weight 48 kg Vesa Mounting 400 x 400 mm B:38| T:38 | L/R:38 mm Bezel Width

110 VAC - 240 VAC Power Supply

ENVIRONMENTAL CONDITIONS

Operating Temperature +40°C / 0°C Operating Humidity 90%

FEATURES

USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up Main Features

IR Touch, Joystick, IR Extender Support, Rocker Switch, Mechanical Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders Features

Optional Features OPS Compliance Speaker 2 x 8 W

ACCESSORY

Typical Deep Standby

QSG, Instruction Book, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable Standard

195 W

≤ 0.5W

POWER CONSUMPTION

CERTIFICATION

Safety YES EMC YES YES CE Reability Approval YES

