

Key Features

Streamlined Desktop Display Solution | Enhanced Producitivity with Dual Monitor Setup | Reduce Clutter with Single-Cable Solution | A More Comfortable Workspace | Command and Control Made Easy

Product **Description**



Designed to boost productivity and maximize output, the ViewSonic[®] VG2756-4K is a 27" 4K Ultra HD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB Type-C connectivity makes setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.



Display:		Video Signal:	
Display Size (in.):	27	Frequency Horizontal:	15 ~ 150 KHz
Viewable Area (in.):	27	Frequency Vertical:	24 ~ 75 Hz
Panel Type:	IPS	Video Input:	
Resolution:	3840 x 2160	Digital Sync:	TMDS for HDMI (v2.0), PCI-E for DisplayPo (v1.2), Micro-Packet for USB Type C
Resolution Type:	4K (3840x2160)	Ergonomics:	
Static Contrast Ratio:	1,000:1	Height Adjust:	130 mm / 5.1 in
Dynamic Contrast Ratio:	50,000,000:1	Swivel:	120°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	350 cd/m2	Tilt (Forward/Back):	40° / 5°
Colors:	1.07B	Weight (imperial):	40-7.5-
Color Space Support:	8+2 bits	Net (lbs):	16.5
Aspect Ratio:	16:9	Net Without Stand (lbs):	10.5
Response Time (Typical GTG):	14ms		
Response Time (GTG w/OD):	5ms	Gross (lbs):	23.6
Backlight Life (Hours):	30,000	Weight (metric):	7.6
Panel Surface:	Anti-glare, Hard coating (3H)	Net (kg):	7.5
Compatibility:		Net Without Stand (kg):	5.1
PC Resolution (max):	3840 x 2160	Gross (kg): 10.7	
Mac [®] Resolution (max):	3840 x 2160	Dimensions (imperial) (WxH)	
Connector:		Packaging (in.):	27.2 x 8.6 x 16.9
USB Type A(2), USB Type B(1), Ethernet LAN (RJ45)(1), HDMI 2.0 In(1),		Physical (in.):	24.1 x 16.0 x 8.0
DisplayPort(1)		Physical Without Stand (in.):	24.1 x 14.3 x 2.0
Audio:		Dimensions (metric) (WxHxD	
Internal Speakers:	2W (x2)	Packaging (mm):	692.0 x 218.0 x 430.0
Power:		Physical (mm):	613.0 x 406.0 x 202.0
Eco Mode (Conserve):	16.8W	Physical Without Stand (mm):	613.0 x 363.0 x 52.0
Eco Mode (optimized):	21.2W	General:	
Consumption (typical):	30.7W	Regulations: cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX CoC, Mexico Energy	
Consumption (max):	70.0W	PACKAGE CONTENTS: VG2756-4K, Power Cable, DP to DP Cable, USB Type C	
Voltage:	AC 100-240V (universal), 50-60Hz	cable, USB Type B Uplink Cable, Quick Start Guide	
Stand-by:	0.5W	Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.	
Power Supply:	Internal	Warranty: Three-year limited warranty on parts, labor and backlight	
Additional Hardware:		UPC: 766907008555	
Kensington Lock Slot:	1		
Controls:			
Physical Controls:	1,2,3,4,5,6 (Power)		
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)		
Operating Conditions:			
Temperature:	32-104° F (0 - 40° C)		
	20.00%		



20-90%

100 x 100 mm

Humidity (non-condensing):

Mount:

VESA Compatible: