Video/Surveillance

S300 Surveillance Hard Drive

Always On, Always Watching



2 4

EMEA Region, Toshiba Storage Solutions - With surveillance systems, nothing but the best is good enough. The Toshiba 3.5-inch S300 is built to meet the highest demands. With support for up to 32 high-resolution surveillance video cameras simultaneously and up to 4 TB capacity, it brings everything into clear view. Each S300 is built with the $\,$ highest-quality components and has passed rigorous tests to ensure 24 x 7 reliability and performance. That's Toshiba quality you can trust under the harshest working conditions.

- Surveillance Digital Video Recorders (sDVR)
- Surveillance Network Video Recorders (sNVR)
- Hybrid sDVR (analog and IP)
- RAID Storage Arrays for Surveillance



3.5" SATA Hard Drive

5400 rpm

128 MB buffer

24/7 operation

Supports up to 32 video cameras

High reliability and enhanced real-time performance

Toshiba Dynamic Cache Technology

(°) Toshiba Stable Platter Technology

High-endurance design

3-year warranty


Manual

Toshiba Installation and Safety.pdf 🕹





Product Specifications



Ra	sic	Si	20	cifi	ca	ti,	n
ра	SIC	31	JE	CIII	ca	u	<i>)</i>

Form factor	3.5-inch		
Interface	6.0 Gbit/s		
Number of cameras supported	32		
Drive bays supported	1 to 8		
Rotational Vibration (RV) Sensors	Yes		
Advanced Format (AF)	Yes		
RoHS compatible	Yes		
Halogen Free	Yes		
Shock Sensor	Yes		

Performance

Rotational speed	5,400 rpm
Max. data transfer speed (sustained)	157 MB/s Typ. (4 TB CMR) 184MB/s Typ. (2TB, 4 TB SMR)
Buffer size	128 MB (2 TB, 4 TB)
Average latency	5,56 ms (2 TB, 4 TB)
Native Command Queing (NCQ)	supported

Reliability

-	
Workloads	110 TB/year (4 TB) 180 TB/year (2 TB, 4 TB)
MTTF	1,000,000 hours
Unrecoverable error rate	1 per 10E14 bits read
24/7 operation	Yes
Load / Unload Cycle	600,000
Limited warranty	3 years

Power Management

7.5 W typ. (4 TB)
4.11 W typ. (4 TB)
4.01 W typ. (2 TB)

Box Content

non-operating)

Box Content	3.5-inch internal hard drive - S300 Surveillance Hard Drive
Physical	
Weight (approx.)	720 g max. (4 TB) 650 g max. (4 TB) 440 g max. (2 TB)
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm
Environmental	
Acoustics (idle mode)	26 dB typ. (4 TB) 22 dB typ. (4 TB) 21 dB typ. (2 TB)
Shock (non-operating)	2940 m/s2 300 G / 2 ms duration (4 TB) 3430 m/s2 350 G / 2 ms duration (4 TB) 3430 m/s2 350 G / 2 ms duration (2 TB)
Shock (operating)	686 m/s2 70 G / 2 ms duration
Vibration (non-operating)	29.4 m/s2 {3.0 G} (5 to 500 Hz)
Vibration (operating)	7.35 m/s2 {0.75 G} (5 to 300 Hz) 2.45 m/s2 {0.25 G} (300 to 500 Hz) (4 TB) 4.90 m/s2 {0.50 G} (5 to 350 Hz) 2.45 m/s2 {0.25 G} (350 to 500 Hz) (4 TB) 4.90 m/s2 {0.50 G} (5 to 350 Hz) 2.45 m/s2 {0.25 G} (350 to 500 Hz) (2 TB)
Temperature (operating /	0 to 70° C / -40 to 70°C

Product Range

 Part number
 Capacity
 Color

 HDWT140UZSVA (CMR)
 4 TB

 HDWT740UZSVA (SMR)
 4 TB

 HDWT720UZSVA (SMR)
 2 TB

Logistical Information:

 $\begin{array}{ll} \text{Box dimensions} & \text{n/A} \\ \text{Box weight (gross)} & \text{n/A} \end{array}$

Master carton dimensions 321 x 406 x 213 mm

Master carton weight (gross) 16 kg (typ.), 11 kg (typ.) (1TB, 500GB)

Boxes per master carton 20
Pallet dimensions n/A
Pallet weight (net) n/A
Units per pallet 180

Contact

Toshiba Electronics Europe GmbH

Hansaallee 181 40549 Düsseldorf Germany