# WorkForce DS-730N Image: Datasheet / BROCHURE Image: Datasheet / Bottop </



# Release the potential of a connected workplace with this affordable and highly efficient standalone network scanner.

Connect your business with this affordable and highly efficient standalone network scanner. It's the intelligent choice for business document management, offering the ability to scan to separate locations – at the touch of a button, allowing you to capture, convert and distribute scanned information within your organisation.

# Shared

Scan to email, folder, FTP, SFTP, cloud services and Microsoft applications at the touch of a button<sup>1</sup>. The control panel with built in 1.44'' colour LCD display and three individual job buttons enables you to choose the correct job and send documents to the right destination without delay, making the digital files available across multiple departments.

# High performance

With a high capacity 100 sheet ADF and scan speeds of up to 40ppm/80ipm, bulk jobs can be captured quickly and easily as a single file, with minimal user intervention.

# Intelligent

Take control with a range of intelligent features, including ultra-sonic sensors and a paper protection function. Slow mode allows difficult media to be captured by reducing roller speed, without increasing file sizes. Double feed detection skip means difficult documents like envelopes and post-it notes can be processed rapidly.

# Reliable

Paper protection, double feed and dirt detection warning ensure high quality digital images are captured carefully and precisely, from 27gsm to 413gsm. The Active Separation Roller System and on-board sensors help prevent document double-feeds and ensures every piece of paper is scanned accurately.

# **KEY FEATURES**

- Standalone network scanning Release the potential of a connected workplace
- File sharing One touch scan to different destinations
- Reliable paper handling Take control with ultra-sonic sensors and paper protection
- Speed with control Use slow mode or scan documents with speeds of up to 40 ppm (80ipm)
- Built-in display Easy to use 1.44 inch colour LCD



#### PRODUCT SPECIFICATIONS

| TECHNOLOGY   |   |
|--|---|
| Scanner Type   | Sheetfed Scanner  |
| Optical Resolution (ADF)   | 600 DPI x 600 DPI (Horizontal x Vertical)   |
| Optical Resolution   | 600 DPI x 600 DPI (Horizontal x Vertical)   |
| Scanning color depth   | Input: 30 Bits Color / 10 Bits Monochrome , Output: 24 Bits Color / 8 Bits Monochrome   |
|  | e 50.8 mm x 50.8 mm (Horizontal x Vertical)   |
|  | e215.9 mm x 6,096 mm (Horizontal x Vertical)  |
| Paper Formats  | A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B4 (25.7x36.4 cm), B5 (17.6x25.7 cm),<br>B6 (12.5x17.6 cm), Letter, Legal, Postcard, Business cards, Plastic cards, DL (Envelope)  |
| SCANNER  |   |
| Optical Sensor   | CIS (Contact Image Sensor)  |
| Light Source   | ReadyScan LED technology  |
| Output Resolution  | 1200 DPI  |
| SCAN SPEED   |   |
| Scanning Speed   | Monochrome: 40 pages/min - Color: 40 pages/min gemessen mit Size: A4 , Resolution: 200 / 300 dpi, Monochrome: 80 image/min - Color: 80 image/min gemessen mit Size: A4 ,  |
|  | Resolution: 200 / 300 dpi   |
| SCANNING FEATURES  |   |
| Features   | RGB colour dropout, Advanced Colour Dropout / Enhance, Skip blank page, A3 stiching,  |
|  | Punch holes removal, Advanced editing, Pre-defined scanning settings, Automatic de-skew,  |
|  | Automatic multi-document recognition, Dual Image Output (Windows only), Auto-rotation, Text   |
|  | enhancement, Edge fill, Barcode Recognition, Manual / Automatic Job Separation, Scan to<br>Cloud Storage  |
| Output formats   | BMP, JPEG, TIFF, multi-TIFF, PDF, searchable PDF, PDF/A, PNG, docx, xlsx, pptx  |
| Advanced document  | Scan to Email, Scan to FTP, Scan to Web folders, Scan to Network folders  |
| integration  | Scan to Linai, Scan to FF, Scan to web louels, Scan to Network louels   |
|  |   |
| CONNECTIVITY   |   |
|  | USB 2.0 Type B, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T)  |
| Interfaces   |   |
| Interfaces<br>GENERAL<br>Supply Voltage  | AC 100 V - 240 V, 50 Hz - 60 Hz   |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions  | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight  | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight  | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro   |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight  | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software   | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating   | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,   |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating<br>Systems  | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,<br>Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP SP3  |
| Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating<br>Systems<br>Supported Humidity   | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,<br>Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP SP3<br>Operation 15% - 80%, Storage 15% - 85%  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating<br>Systems<br>Supported Humidity<br>Supported Temperature   | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,<br>Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP SP3  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating<br>Systems<br>Supported Humidity<br>Supported Temperature<br>PAPER / MEDIA HANDLING                           | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,<br>Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP SP3<br>Operation 15% - 80%, Storage 15% - 85%  |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating<br>Systems<br>Supported Humidity<br>Supported Temperature<br>PAPER / MEDIA HANDLING<br>Paper Setting Capacity | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,<br>Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP SP3<br>Operation 15% - 80%, Storage 15% - 85%<br>Operation 5° C - 35° C, Storage 25° C - 60° C |
| Interfaces<br>GENERAL<br>Supply Voltage<br>Product dimensions<br>Product weight<br>Included Software<br>Compatible Operating<br>Systems<br>Supported Humidity<br>Supported Temperature<br>PAPER / MEDIA HANDLING                           | AC 100 V - 240 V, 50 Hz - 60 Hz<br>296 x 169 x 167 mm (Width x Depth x Height)<br>3.6 kg<br>Epson Device Admin, Epson Document Capture (Mac only), Epson Document Capture Pro<br>(Windows only), Epson Document Capture Pro Server (on free download), Epson Event<br>Manager, Epson Scan 2, Web browser interface<br>Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003,<br>Windows Server 2008 (32/64bit), Windows Server 2012 R2, Windows Vista, Windows XP SP3<br>Operation 15% - 80%, Storage 15% - 85%<br>Operation 5° C - 35° C, Storage 25° C - 60° C |

# LOGISTICS INFORMATION

| ѕки               | B11B259401BY  |
|-------------------|---------------|
| EAN code          | 8715946679211 |
| Country of Origin | Indonesia     |

For more information please contact:

Home users: 0343 90 37766 Business users\*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus \* 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2020-11-09

# WorkForce DS-730N

# WHAT'S IN THE BOX

- Power cable
- Main unit
- Warranty card
- Setup guide
- AC adapter
- USB cable
- Driver and utilities (CD)

#### **OPTIONAL ACCESSORIES**

- Roller Assembly Kit Advanced
   B12B819711
- Carrier Sheet (set of 5) B12B819051
- Cleaning Kit B12B819291

1.  $\ensuremath{\,^1\text{Some}}$  features require the use of Epson software packages.

