





DC-F80 4K Document Camera











The Lumens[®] DC-F80 Ladibug[™] document camera comes with impressive 4K 30fps image resolution quality with 30x total zoom. It can demonstrate detailed images of any objects in real-time. The shooting area is up to A3 paper size with three brightness levels LED light enhancing content readability. The DC-F80 makes teaching more interactive and powerful.

Key Features

- Impressive 4K 30fps image quality
- 2-in-1 solution with document camera and webcam
- Image rotation 0° / 90° / 180° / 270° / Flip / Mirror
- LED light with three brightness levels

Key Feature Details



2-in-1 Solution

You can use the document camera, such as a teaching webcam, present teaching materials, and interact with students via flexible joints and arms.



Excellent Image Quality

The DC-F80 camera delivers 4K 30fps image quality with 30x total zoom. It can demonstrate detailed images of any objects in real-time.



Easy-to-Use

Pressing one button to capture, record and rotate image with intuitive panel gets the perfect image quality with ease.



Ladibug™ 4K Software

Lumens Ladibug™ 4K Software is equipped with live annotation, mask, spotlight, and recording functions. Allows you to engage the audience easily.

Applications







Education



Distance Learning

Product Specifications

Total Pixels 3840 x 2160 Output Resolution 4K(2160p), 1080p, 720p, XGA Frame Rate 1080p 30/60 fps 2160p / 720p / XGA 30/25 fps Sharpness MTF 1100 line Close-up 10 cm Zoom Total 30x (Maximum) Mechanical Zoom 3.4x Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Auto Tune Yes, One Button for Optimization Image		1
Output Resolution 4K(2160p), 1080p, 720p, XGA Frame Rate 1080p 30/60 fps 2160p / 720p / XGA 30/25 fps Sharpness MTF 1100 line Close-up 10 cm Zoom Total 30x (Maximum) Mechanical Zoom 3.4x Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Auto Tune Yes, One Button for	Sensor	1/3" 13MP CMOS
Frame Rate 1080p 30/60 fps 2160p / 720p / XGA 30/25 fps Sharpness MTF 1100 line Close-up 10 cm Zoom Total 30x (Maximum) Mechanical Zoom 3.4x Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes, One Button for	Total Pixels	3840 x 2160
Sharpness MTF 1100 line Close-up 10 cm Zoom Total 30x (Maximum) Mechanical Zoom 3.4x Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Output Resolution	4K(2160p), 1080p, 720p, XGA
Close-up Zoom Total 30x (Maximum) Mechanical Zoom 3.4x Shooting Area Max. Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes, One Button for	Frame Rate	
Zoom Total 30x (Maximum) Mechanical Zoom 3.4x Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Sharpness	MTF 1100 line
Mechanical Zoom 3.4x Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Close-up	10 cm
Shooting Area Max. 16.5" x 12.4" (420mm x 316mm) Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Zoom	Total 30x (Maximum)
Lamp LED Lamp Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Mechanical Zoom	3.4x
Arm Mechanical Joint Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Shooting Area Max.	16.5" x 12.4" (420mm x 316mm)
Power USB Bus Power, 5V 1~0.45A Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Lamp	LED Lamp
Output HDMI x1 / USB 2.0 Control USB Built-in Microphone Yes Yes, One Button for	Arm	Mechanical Joint
Control USB Built-in Microphone Yes Yes, One Button for	Power	USB Bus Power, 5V 1~0.45A
Built-in Microphone Yes Yes, One Button for	Output	HDMI x1 / USB 2.0
Auto Tune Yes, One Button for	Control	USB
Auto line	Built-in Microphone	Yes
	Auto Tune	
Focus Mode Auto / Manual	Focus Mode	Auto / Manual
Image Mode Photo / Text	Image Mode	Photo / Text

Image Rotation	0° / 180° / 90° / 270° / Flip / Mirror
Video/Audio Recording	Ladibug™ Software
Freeze	Yes
Pan	Yes
USB Image Transmission	USB 2.0 (480 Mbps) High Speed Transmission
Image Capture	Ladibug™ Software
Driver	UVC / UAC
Free Lumens® Software	Supports Windows 10, 8, 7, Mac OS X, Chrome OS
Anti-Theft	Kensington Anti-Theft Lock Device
VESA Mount	Yes
Included Accessories	USB Cable
Power Consumption	5W (Maximum)
Weight	2.65 lbs (1.2 kg)
Dimensions	Folded: 5.4" x 5.5" x 10.6" (137 x 140 x 270 mm) Open: 12" x 5.5" x 14.7" (306 x 140 x 373 mm)

Compatible Software


















Google Meet



User Interface

Kensington Lock Slot





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone: +1-866-600-0988 Fax: +1-510-252-1389

Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone: +32-473-58-38-95 Fax: +32-2-452-76-00

