HANNspree

HO 245 PTB 23.8" Open Frame Touch Monitor

Experts in **Display**

Open Frame Touch Monitor

HO 245 PTB

23.8" / 60,45cm Diagonal LED Backlight – Format 16:9

- 1920 x 1080 Resolution Full HD 1080P
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- Triple Input: DP + HDMI + VGA
- Built-in Speakers
- IP65 Rating Level
- Display Protection: Thickness 3mm
- ≥7H Toughened Hard Panel Surface
- Built for 24/7
- VESA Mount
- Orientation: Landscape, Portrait, Face-Up









23.8" / 60,45 cm

Part. No..: HO 245 PTB

SIZE, RESOLUTION

23.8"

23.8"

16:9 Aspect Ratio



Full HD 1920 x 1080

CONNECTIVITY, IP LEVEL



DP HDMI VGA



IP 65 Water & Dust Protection

VIEWING ANGLE, VESA



178 Ultra-Wide Viewing Angle



VESA Mount

OTHER FEATURES



10 Points Touch



Built for 24/7 Operation

Technical Specifications >>>

* For more details contact your local HSP office / representative or send us a request via the product enquiry form on the website.



HO 245 PTB 23.8" Open Frame Touch Monitor

Experts in **Display**

Display Size	60.45 cm / 23.8" Diagonal
Panel Type	TFT – LED Backlight, ADS Panel (*)
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	350 cd/m ² (Panel) – 285 cd/m ² (Monitor)
Contrast	1.000:1 (Typical) – 5.000.000 (Active Contrast)
Viewing Angle L/R; U/D	178° H / 178° V (CR > 10)
Response Time	5 msec
Pixel Pitch	0,2745 (H) x 0,2745 (V) mm
Touch Type	Projected Capacitive – 10 Point Touch Type: Cover Glass + LOCA + ITO Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	VGA
Input 2	HDMI
Input 3	Display Port
Input 4	USB 2.0 (Touch)
Speakers	Yes, 2W x 2, Earphone jack
Power Consumption	On: 35W; Stand-by: ≤0,5W; Off: ≤0,3W (TBC)
Power Range	Built-In Power Supply AC 100 ~ 240 Volt; 50 ~ 60 Hz
Product Dimensions	549 x 55 x 333 mm (W x D x H) TBC
Packing Dimensions	630 x 123 x 439 mm (W x D x H) TBC
Net / Gross Weight	- Kg / - Kg TBC

VESA Mounting	100 x 100 mm
Display Protection	Thickness 3.0±0.3 mm
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥85%
IP Rating Level	IP 65 on surface (Front), Water and Dust Protection **
Controls	Power, Auto, (+), (-), Menu
Color	5500K, 6500K, 9300K, User Modes
Preset Mode	PC, Movie, Game, ECO Modes
On Screen Display	11 Languages
Accessory	Power Adaptor; EU and UK Power cables (1.5 mt); HDMI Cable (1.5m); USB 2.0 (B-A) Cable for Touch (1.8m); Quick Start Guide; Warranty Card
Orientation	Landscape, Portrait, Face-Up
24 / 7	Yes

PART. NO.:

* "ADS" word mark / trademark and related patents

on technologies belong to their respective owners.

HO 245 PTB

^{© 2020} HANNSpree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.