



Unleash your full gaming potential with the Fast IPS GB2570HSU Red Eagle

Get the competitive edge you need to unleash your full gaming potential with the 24.5" GB2570HSU offering 0.5ms MPRT and 165Hz refresh rate. Armed with FreeSync Premium you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas and the IPS panel technology guarantees superb image quality. Thanks to the height adjustable stand you can easily adjust the screen position to your preferences to ensure comfort during marathon gaming sessions.



Fast IPS

The Fast IPS panel technology guarantees not only high-fidelity, vivid battleground scenes displayed with outstanding colour accuracy but provides also an outstanding 0.5ms Moving Picture Response Time (MPRT).



FreeSync™ Premium Technology

This monitor guarantees low input latency and low framerate compensation putting an end to any tearing or stuttering issues at virtually any framerate.

DISPLAY CHARACTERISTICS

Diagonal	24.5", 62.2cm
Panel	Fast IPS, matte finish
Native resolution	1920 x 1080 @165Hz (2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	400 cd/m²
Static contrast	1000:1
Advanced contrast	80M:1
_	
Response time (MPRT)	0.5ms
Response time (MPRT) Viewing zone	0.5ms horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
, ,	
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Viewing zone Colour support	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° 16.7mln 8bit
Viewing zone Colour support Horizontal Sync	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° 16.7mln 8bit 30 - 184kHz

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.2.0, max. 1920 x 1080 @165Hz) DisplayPort x1 (v.1.4, max. 1920 x 1080 @165Hz)
USB HUB	x2 (v.3.0 DC5V, 900mA)
HDCP	yes
Headphone connector	yes



Blue light reducer	yes
Flicker free	yes
FreeSync support	HDMI: 1920 x 1080 @40-165Hz, DP: 1920 x 1080 @40-165Hz
HDR	HDR Ready
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu/ Select, +/ Volume, -/ ECO, Exit, Input Select
User controls	picture adjust (contrast, brightness, overdrive, ACR, ECO, blue light reducer, Black Tuner, colour saturation, MBR, gamma), input select, audio adjust (volume, mute), store user settings, colour settings (colour temperature, 6-Axis, user preset), image adjust (i-Style colour, X-Res Technology, sharp & soft, RGB range, video mode adjust), language, setup menu (OSD H. position, OSD V. position, OSD rotation, OSD time out, opening logo, AMD FreeSync Premium, LED), display information, reset
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX



04 MECHANICAL

Display position adjustments	height, pivot (rotation), tilt
Height adjustment	130mm
Rotation (PIVOT function)	90°
Tilt angle	18° up; 3° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC AC - 100V, 240/V, 50Hz
Power usage	21W typical, 0.5W stand by, 0.5W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
,	
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	557.5 x 391.5(521.5) x 256mm
Box dimensions W x H x D	711 x 420 x 214mm
Weight (without box)	4.5kg
Weight (with box)	6.5kg
EAN code	4948570118311



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED