HANNspree

15.6" USB Type-C Portable Monitor

Experts in **Display**

HL 162 CPB 39,6 cm / 15.6" Diagonal LED Backlight – Format 16:9

Create a dual-display mobile workspace almost anywhere with the HANNspree 15.6" Portable Monitor. ...adding a second monitor has never been so easy.

- 1920 x 1080 Resolution
- Full HD 1080p
- 170° / 170° Wide Viewing Angle
- USB 3.1 Type-C x 2 (Power Supply & Signal)
- Mini-HDMI and Micro-USB 2.0
- Built-in Stereo Speakers
- Low Blue Light Mode and Flicker Free
- Ultra-slim and sleek ultra-portable design
- Lightweight protective cover foldable stand



Part. No..: HL 162 CPB

SIZE, RESOLUTION	CONNECTIVITY	OTHER FEATURES
15.6" 15.6" 16:9 Aspect Ratio	USB 3.1 USB Type-C x 2	Built-In Stereo Speakers 170°/170° Wide View Angle
Full HD 1920 x 1080 1920 x 1080	Mini-HDMI Mini HDMI	Ultra-Slim Bezel and thin profile

Display Solutions

Technical Specifications >>>

HANNSpree

15.6" USB Type-C **Portable Monitor**

HANNspree

Experts in **Display**

Display Size	39,6 cm / 15.6" Diagonal	
Panel Type	TFT – LED Backlight Technology (ADS Panel*)	
Aspect Ratio	16:9	
Resolution (H x V)	1920 x 1080 Full HD	
Brightness	250 cd/m² (Typical)	
Contrast (Typ.)	800:1 (Typical)	
Contrast (Active)	10.000.000:1 (Active)	
Viewing Angle L/R; U/D	170° H / 170° V (CR > 10)	
Response Time	15 msec	
Pixel Pitch	0.17925 (H) X 0.17925 (V) mm	
Display Colors	16.2M Colors (6-bit + FRC), Color Gamut: 47% NTSC	
Panel Surface	Fine Anti-Glare	
Horizontal Frequency	30 ~ 81 kHz	
Vertical Frequency	56 ~ 75 Hz	
Max Display Frequency	1920 x 1080 @ 60Hz	
Input 1	USB 3.1 Type-C x 2 (Power Supply & Signal) USB 3.1: Power Supply Standard 20V/5A Transmission rate: 10Gbps	
Input 2	Mini HDMI 1.4 x 1	
Input 3	Micro USB 2.0 x 1	
Speakers	Yes, 1W x 2; Earphone Jack	
Power Supply	USB 3.1 Type-C (DC Output PD 20V/5A)	
Power Consumption	On: 7,4W; Stand-by: 0,3W; Off: 0,2W	
Product Dimensions	367,7 x 10,5 x 225 mm (W x D x H)	
Packing Dimensions	390 x 55 x 262 mm (W x D x H)	
Net / Gross Weight	- Kg / - Kg TBC	

VESA Mounting N/A Tilt / Swivel NA / N/A Kensington Lock N/A MENU / + / - / EXIT **Control Button** Color Cool, Warm, Normal, User Modes Preset Mode Standard, Game, Movie, ECO Modes **On Screen Display** 16 Languages Type-C to Type-C Cable (1m); HDMI – Mini HDMI Cable (1m); Warranty Card; Quick Start Guide; Accessories Protective Foldable Stand Case **Other Features** Low Blue Light Mode / Flicker Free

ENERG [*]	ENERG [*]	Sup
spree HL162CPB(HSG1444)	HANNSpree HL162CPB(H5G1444)	Мо
		Ene Dyi
		Anı (kV
7 kWh/1000h	G 7 kWh/1000h	On Dyr
		Off
		Sta
1920 px	1920 px	Scr
16.000 px	1991 1991 1991 1991 1991 1991 1991 199	Res

Supplier's Name	HANNspree
Model Name	HL162CPB
Energy efficiency class for standard Dynamic Range (SDR)	С
Annual Energy Power Consumption (kWh/1000h)	7 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	7,4 W
Off mode power demand (W)	0,2 W
Standby mode power demand (W)	0,3 W
Screen Diagonal (cm / inches)	39,6cm / 15.6"
Resolution	1920 x 1080



© 2021 HANNSpree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies

HANNspree

15.6" USB Type-C Portable Monitor

Experts in **Display**







