

i-tec USB 3.0 / USB-C Dual Display Docking Station HDMI DVI + VGA

i-tec USB 3.0 / USB-C Dual Display Docking Station HDMI DVI + VGA



PRODUCT DESCRIPTION

A universal docking station that can be used with virtually any laptop, as it supports connection to all common ports: USB 3.0, USB-C and Thunderbolt 3/4, while supporting all common current operating systems.

The station supports up to 2x external monitors, which you can connect via HDMI and DVI ports. 6x USB ports (two of which are USB 3.0), reliable and fast internet connectivity thanks to the integrated LAN port and audio input and output support.

The docking station can also be installed behind the monitor with VESA mounting support (thanks to the <u>VESA bracket</u> that comes separately), giving you both maximum work efficiency thanks to the expandability of the ports and a beautifully tidy desk without cables.

- Connect up to two external monitors
- HDMI and DVI ports are available, or VGA with the included adapter
- 2x USB 3.0 (including one with fast charging support) for fast data transfer
- 4x USB 2.0 allows you to easily connect your USB devices and peripherals.
- Gigabit Ethernet RJ-45 provides reliable, robust, high-speed Internet connectivity with support for 10/100/1000 Mbps speeds
- Separate audio output and audio input (microphone)

Supports Windows 10, macOS X, Android, ChromeOS and Linux

PRODUCT FEATURES

- 1x USB 3.0 port for connection to devices
- Docking station technology: <u>DisplayLink</u>
- · Video ports:
 - 1x HDMI
 - 1x DVI
 - 1x VGA (Adapter)
- Resolution:
 - ∘ 1 monitor 1x HDMI \rightarrow up to 2560×1440/50Hz
 - 1 monitor 1x DVI → up to 2048×1152/60Hz
 - 1 monitor 1x VGA → up to 1920x1080/ 60 Hz
 - 2 monitors 1x HDMI + 1x DVI → up to 2x 2048×1152/60 Hz
 - 2 monitors 1x HDMI + 1x VGA → up to 1x 2048×1152/60 Hz + 1x 1920x1080/60Hz
- 1x USB 3.0 port
- 1x USB 3.0 port with fast charging support (BC 1.2)



- 4x USB 2.0 port
- 1x Ethernet GLAN RJ-45 port (DisplayLink DL-3900)
- 1x 3.5mm Audio output, 1x 3.5mm Microphone input
- 1x power input (DC 12V/2A)
- LED indication
- Support for Kensington lock
- Support for VESA mounting
- USB-A to USB-B cable (80cm)
- USB-C to USB-B cable (80cm)
- OS: Windows 7/8/8.1/10, macOS, Linux Ubuntu 14.04 or later, Android 5 or later, Chrome OS R51 or later
- Easy driver installation (Windows, MacOS, Ubuntu, Android (external link))
- Product dimensions: 226 x 77 x 28 mm
- Product weight: 760 g
- Package dimensions: 338 x 150 x 58 mm

Hardware requirements:

• Device with a free USB-A, USB-C or Thunderbolt 3/4 port

Operating System:

• Windows 7/8/8.1/10, macOS, Linux Ubuntu 14.04 or later, Android 5 or later, Chrome OS R51 or later

SPECIFICATION

| Part Number | Product Description & EAN | |
|---------------------|---|--|
| CAHDMIDVIDOCKPRO | i-tec USB 3.0 / USB-C Dual Display Docking Station HDMI DVI + VGA EAN: 8595611704079 | |
| CAHDMIDVIDOCKPROUK | i-tec USB 3.0 / USB-C Dual Display Docking Station HDMI DVI + VGA EAN: 8595611704109 | |
| Hardware | | |
| Bus type | USB-C, USB-3.0, Thunderbolt-3 | |
| Ports/Connectors | | |
| System Requirements | | |
| Operating system | Windows 7 / 8 / 8.1 /10 macOS X Android 5 or later Linux Ubuntu 14.04, 16.04, 17.04, 17.10, 18.04, 19.04 Chrome OS R51 or laterWindows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically. | |
| Other features | | |
| Colour | black | |
| Housing Material | ABS | |
| Product Dimensions | 226 x 77 x 28 mm | |
| Product Weight | 760 g | |



| Package Weight | |
|---|-------------------|
| Packaging Dimensions (LxWxH) | 338 x 150 x 58 mm |
| Support | |
| Warranty period | 2 years |
| Technical support | lifetime |
| Package contents | |
| Product | |
| Power adapter | |
| USB-B to USB-A connection cable (80 cm) | |
| USB-B to USB-C Connection Cable (80 cm) | |
| Manual | |

For further information regarding setup or for answers to FAQ's, please visit our website <u>i-tec.pro</u>. Specifications are subject to change without notice.

Updated 11.6.2021