





MODUS 3 PRESENTER

MODUS 3 PRESENTER

Small footprint kiosk printer

Ultra compact thermal printer with presenter, to meet the needs of slim-line kiosks without sacrificing features and functionality. MODUS 3 PRESENTER joins all the features of a self-service printer with an inimitable compactness and the capability of a performing loop presenter. It's super-light and full opening lid, easy to inspect mechanism, guarantees easier maintenance.





CHARACTERISTICS

- Ultra compact, the smallest footprint printer with presenter on the market
- Flexibility extended working temperature and adjustable paper width
- Easy integration (plug&play) in all self-service applications
- Loop paper management: up to 30 cm
- Max control set up the printer or design a ticket layout with our apps
- Adjustable guides for paper width
- Connectors label
- Easy opening (with cover open sensor)
- Paper end sensor and black mark detection (non thermal side)
- 24v power supply port, mini-usb port, serial port (external status led and external feed key)
- Optional paper mouth (this option precludes the use of partial cut, only total cut)

MARKETS:

- Automatic Vending Machine
 - Self-Service
 - Info Kiosk
 - Self-Payment
 - QMS
 - Parking
-

ACCESSORIES

- Roll holder with paper roll from above, below or behind (8 positions)
 - Serial cable with feed button and LED
 - Power supply and cables
-

Printing Method

Thermal, fixed head

Number of dots	8 dot/mm
Resolution	203 dpi
Printing speed	200 mm/s
Ejector speed	200 mm/s
Character set	PC437, PC850, PC858, PC860, PC862, PC863, PC864, PC865, PC866, international
Supported Barcode	UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCode
Printing Format	Height/Width from 1 to 8, bold, reverse, underlined, italic
Printing Direction	Normal, 90°, 180°, 270°
Paper width	from 54 to 82.5 mm
Paper weight	from 58 to 116 g/m ²
Paper thickness	from 63 to 120 μm
Printing width	from 48 to 80 mm
Roll Dimension	max. 80 mm
Sensors	Head temperature, paper presence, black mark, cover open, external low paper (optional)
Emulation	CUSTOM/POS
Interfaces	USB 2.0 full speed RS232 Serial
Buffer	1 kB
Flash Memory	768 kB internal
RAM Memory	128 kB internal
Graphics Memory	1 logo (640x409 dot)
Drivers	Windows XP VISTA (32/64 bit) Windows 7 (32/64 bit) Windows 8 (32/64 bit) Windows 8.1 (32/64 bit) Windows 10 (32/64 bit) Driver autoinstallante per Virtual COM (32/64 bit) Linux
Power supply	24 Vdc ± 10% (optional external power supply)
Medium consumption	0.89 A
Head Life	150 Km / 100 Millions pulse (with recommended paper)
MCBF	Reliable cutter with total cut : 1M cuts
Operating temperature	from -20°C to +70°C
Dimensions	96(L) x 62.6(H) x 116.3(W) mm 203.6(L) x 147.5(H) x 132.6(W) mm with paper roll holder
Weight	614 g

MODELS



915LF010700300

PRINTER MODUS 3 USB RS232
WITH PRESENTER

CUSTOM S.P.A. - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE:
8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.
Last update: 06 October 2021