

OVERVIEW



1. Power button	5. USB4
2. Headphone / microphone combo jack (3.5mm)	6. USB4
3. USB-C 3.2 Gen 2	7. SD card reader
4. Kensington Nano Security Slot	

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 5 / 7 / 9 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen 5 PRO 6650H	6	12	3.3GHz	4.5GHz	3MB L2 / 16MB L3	LPDDR5-6400	AMD Radeon™ 660M Graphics
AMD Ryzen 7 PRO 6850H	8	16	3.2GHz	4.7GHz	4MB L2 / 16MB L3	LPDDR5-6400	AMD Radeon 680M Graphics
AMD Ryzen 9 PRO 6950H	8	16	3.3GHz	4.9GHz	4MB L2 / 16MB L3	LPDDR5-6400	AMD Radeon 680M Graphics

Operating System

Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- Fedora Linux
- Linux
- Ubuntu Linux
- No operating system

Graphics

Graphics**

Graphics	Type	Memory	Key Features
AMD Radeon 660M	Integrated	Shared	DirectX® 12
AMD Radeon 680M	Integrated	Shared	DirectX 12
AMD Radeon RX 6500M	Discrete	4GB GDDR6	DirectX 12

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays (native display and 3 external monitors via USB4® or USB-C®)

- USB4 supports up to 8K@30Hz
- USB-C supports up to 4K@60Hz (4 displays output), 5K@60Hz (3 displays output) or 5K@120Hz (up to 2 displays output)

Notes:

1. 8K resolution support needs 2 display pipes. That is, simultaneous display number will "-1" when 8K resolution displayed.

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR5-6400

Notes:

- The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^[1]

One drive, up to 2TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe® Gen 4x4 slot, supports M.2 2242/2280 SSD

Storage Type**

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe NVMe®, PCIe 4.0 x4	256GB	Opal2
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4 Performance	512GB / 1TB / 2TB	Opal2

Notes:

- The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Card Reader

SD card reader, supports UHS-II SD card

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

Stereo speakers, 2W x2, Dolby® Atmos®

Microphone

Dual array microphone, 360° far-field, Dolby Voice

Camera**

- IR & FHD 1080p hybrid, with E-camera shutter, fixed focus
- IR & FHD 1080p discrete, MIPI, with E-camera shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 72Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Battery Life^[1]

Configuration 1 (max battery life)

MobileMark® 2018: up to 20.5 hr with 657 performance score @200nits

JEITA 2.0: up to 25.9 hr @150nits

Local video playback: up to 29.2 hr @150nits

Alternate configuration 2

MobileMark 2018: up to 19.4 hr with 635 performance score @200nits

MobileMark 25: up to 19.0 hr with 524 performance score @250nits

JEITA 2.0: up to 25.6 hr @150nits

Local video playback: up to 24.6 hr @150nits

Alternate configuration 3

MobileMark 2018: up to 7.7 hr with 619 performance score @200nits

MobileMark 25: up to 6.9 hr with 485 performance score @250nits

JEITA 2.0: up to 9.1 hr @150nits

Local video playback: up to 13.6 hr @150nits

Notes:

1. Configuration 1 (max battery life): WUXGA (non-touch), AMD Ryzen 7 PRO 6850H, 16GB LPDDR5, Win 11, 72Wh battery, best power efficiency power mode
 Alternate configuration 2: WUXGA (touch), AMD Ryzen 7 PRO 6850H, 16GB LPDDR5, Win 11, 72Wh battery, best power efficiency power mode
 Alternate configuration 3: WQUXGA OLED (touch), AMD Ryzen 5 PRO 6650H, 16GB LPDDR5, Win 11, 72Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark 2018](#), [MobileMark 25](#), JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary and depends on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to [Microsoft® link](#) for more information about the Windows Performance power slider.

Power Adapter

Power Adapter^[1]

135W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

1. AC adapter offerings depend on the country.

DESIGN

Display

Display^{**[1]}

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
16.0"	WUXGA (1920x1200)	None	IPS	400 nits	Anti-glare	16:10	1000:1	100% sRGB	Horizontal: +/- 89°, vertical: +/- 80°	Low power, TÜV Low Blue Light, 92.3% screen to body ratio
16.0"	WUXGA (1920x1200)	On-cell touch	IPS	400 nits	Anti-reflection, Anti-smudge	16:10	1000:1	100% sRGB	Horizontal: +/- 89°, vertical: +/- 80°	Low power, TÜV Low Blue Light, 92.3% screen to body ratio
16.0"	WQUXGA (3840x2400)	OGS touch	OLED	SDR 400nits, HDR 500nits	Anti-reflection, Anti-smudge	16:10	100000:1	100% DCI-P3	Horizontal: +/- 87.5°, vertical: +/- 87.5°	Dolby Vision™, TÜV Low Blue Light, 92.3% screen to body ratio

Touchscreen^{**}

- OGS (One Glass Solution) multi-touch, supports 10-point touch
- On-cell touch, supports 10-point touch
- Non-touch

Notes:

1. California Electronic Waste Recycling Fee
 In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Pen

No pen (pen sold separately)

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

LED backlight

UltraNav™

TrackPoint® pointing device and glass surface multi-touch Haptic ForcePad, 67 x 120 mm (2.64 x 4.72 inches)

Mechanical^[1]**Dimensions (WxDxH)**

354.4 x 237.4 x 15.8 mm (13.95 x 9.35 x 0.62 inches)

Weight

Models	Weight
Non-touch models	Around 1.81 kg (3.99 lbs)
Multi-touch models	Around 1.94 kg (4.27 lbs)

Case Color

Arctic grey (top), black (bottom)

Case Material

Aluminium (top), aluminium (bottom)

Notes:

1. The system dimensions and weight vary depending on configurations.

CONNECTIVITY**Network****Onboard Ethernet^[1]**

No Ethernet

WLAN + Bluetooth®^{[2][3]}

Qualcomm® NFA-725A Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2

WWAN**

- Integrated Mobile Broadband 4G LTE, Quectel EM05-G, CAT4, M.2 card
- Fibocom L860-GL-16, 4G LTE CAT16, M.2 card
- No support

SIM Card

- Gemalto eSIM
- No SIM card inbox

NFC

No support

Notes:

1. Ethernet support via optional Lenovo USB-C to Ethernet Adapter
2. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
3. Wi-Fi 6E full features might be limited by country level restrictions.
Wi-Fi 6E only enabled on Windows 11 and operates as Wi-Fi 6 with Windows 10.
6GHz Wi-Fi 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi 6E, and the regional regulatory certifications & spectrum allocation.

Ports^[1]**Standard Ports**

- 1x USB-C 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4a)
- 2x USB4 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort 1.4a)
- 1x SD card reader
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x Nano-SIM card slot (WWAN support models)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3/4: 40 Gbit/s

Docking

Docking

Various docking solutions supported via USB-C.

For more compatible docking solutions, please visit [Docking for ThinkPad® Z16 Gen 1](#)

Monitor Cable

Monitor Cable

- Lenovo USB-C to HDMI® Adapter
- No monitor cable

SECURITY & PRIVACY

Security

Security Chip**

- Discrete TPM 2.0, TCG certified, with Microsoft Pluton TPM 2.0 integrated in chipset
- Microsoft Pluton TPM 2.0 integrated in chipset

Physical Locks

Kensington® Nano Security Slot, 2.5 x 6 mm

Smart Card Reader

No smart card reader

Fingerprint Reader

Touch style fingerprint reader in keyboard key, match-on-chip

BIOS Security

- Power-on password
- Supervisor password
- System management password
- NVMe password
- USB FIDO (Fast Identity Online) device integration
- Certificate based BIOS authentication
- Self-healing BIOS

Other Security

- E-Camera shutter
- IR camera for Windows Hello
- Mirametrix Glance

MANAGEABILITY

System Management

System Management

- DASH
- Non-DASH

SERVICE

Warranty

Base Warranty**^[1]

- 1-year depot service
- 1-year depot with 2-year system board service (Korea only)

- 1-year limited onsite service
- 3-year (1-yr battery) depot service
- 3-year (1-yr battery) limited onsite service
- No base warranty

Notes:

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>

ENVIRONMENTAL

Sustainability

Material

75% post-consumer recycled aluminum
97% PCC recycled plastic used in speaker enclosure
97% PCC recycled plastic used in the 70Wh battery
Low-temperature solder
90% recycled and/or sustainable packaging

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories^{*}**

- Lenovo USB-C to Ethernet Adapter
- Lenovo USB-C to USB-A Adapter
- None

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- ErP Lot 3
- TCO Certified 9.0
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

TÜV Rheinland® Low Blue Light

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD



AMD



AMD



AMD



AMD



AMD